

Hotrun X24



Can serve multiple Handwash Basins, Showers and Kitchen Sinks simultaneously

3-Phase power connection (no neutral required)

Dimensions	480 x 243 x 120 mm		
Power rating	12 kW / 18 kW / 24 kW		
Voltage	415 V		
Current	3 x 16 / 3 x 25 / 3 x 35 Amp		
IP rating	IP24		
Connection	1/2" BSP		
Weight	6 kg		
Performance (at $\Delta T = 25^{\circ}\text{C}$) (Voltage needs to be 415V)	Set to 12 kW	Flowrate 8 L/min	415V-3x16Amp
	Set to 18 kW	Flowrate 11 L/min	415V-3x25Amp
	Set to 24 kW	Flowrate 14 L/min	415V-3x35Amp
Inlet pressure rating	1 MPa (tested at 2MPa)		

Variable programmable power setting, 12, 18 and 24 kWatt

Variable programmable temperature limiter can be set to any required temperature

Variable temperature setting by the end user (below limiter temperature)

Built-in Legionella cleaning cycle program, patented by Elwa Australia

Can be used as a booster in stallations solar or heat pump systems

Tip: Allow 100mm on sides for cord etc and 100mm top and bottom for water connections to allow the cover to be opened after installation

Tip: Base your model & power selection on the winter inlet water temperature

Tip: Position within 6 metres of outlet if possible to minimise legionella risk in downstream hot water pipework



Features

1. Silent, noise-free operation
2. Variable power supply selection (kW)
3. Energy efficient, only uses power when there is demand for hot water
4. Built in temperature limiter
5. Digital display and temperature control
6. Remote life time monitoring option for reporting and full diagnostics
7. Full diagnostics in display
8. Can be installed anywhere
9. Pressure resistant up to 2MPa (leak free guarantee for 10 years)
10. 10 year warranty with option for service agreement

