CABERO Heat Exchanger Yantai Co.,Ltd.
No.178 Xing Fu Zhong Road, Yantai, China,
Tel +86 535 6858102 Fax +86 535 6858119
e-mail: zhu@cabero.cn http://www.cabero.de

Reference		Date 2021.05
Room Size		
Model	**BCH4E1/50J.N6**	Version: 1

Capacity		9831	W
Sensible Capacity		6867	W
Latent Capacity		2964	W
Sensible/Total Capacity Ratio		0.70	
Quantity of Produced Water		4	kg/h
Exchange Surface		76.4	m²
Global Exchange Coefficient		22.2	W /(m² k)
Fins / Tubes Meterial		Al / Copper	
Fin Thickness		0.2	mm
Fin Pitch		4	mm
DTML		5.8	°C
Coil Internal Volume		17	L
L x W x H		1530*780*780	mm
Net Weight			kg
Air side			
Altitude		0	m
Volumetric Air Flow		7500	m³/h
Mass Air Flow		9599	kg/h
Face Velocity on the Coil		2.76	m/s
Inlet Air Density		1.28	kg/m³
Inlet Air Temperature		2	°C
Inlet Air Relative Humidity		90	%
Outlet Air Temperature		-0.5	°C
Outlet Air Relative Humidity		96	%
Pressure Drop		96	Pa
Fan No. * Size		500	mm
Motor Capacity		0.74	kW, 400V-3Ph-50Hz
Run speed		1290	RPM
Noise power lever		74	dB(A)
Defrost			
REFRIGERANT SIDE			
Fluid		Ethylene glycol 35%	
Volumetric Fluid flow		1.6	m³/h
Mass Fluid Flow		1688	kg/h
Fluid Velocity		0.67	m/s
Fluid inlet Temperature	φ 22.0	-8	°C
Fluid outlet Temperature	φ 22.0	-2.1	°C
Fluid Pressure Drop		42	kPa

Accessories