





Milli Pure Progressive Dual Mixer System

FIT OFF



DRESS FINISHING AND HANDLE ADJUSTMENT

Prior to fit off ensure the correct size cut out around the Mixers (100mm centres) has been achieved.(see Fig.1)
 Remove the protective Cover from the Mixer. Ensure the Oring is intact and the installation is clean and free from any debris.
 Apply sealant to the outside of the Cover Flange and fit to the Mixer until the shoulder of the Flange meets the finished Wall.

Fit the Handles onto the Adjustment Fitting.
 If adjustment is required, remove the Handles and loosen the Set Screws of the Adjustment Fitting.
 Wind the Adjustment Fitting to reduce or increase the gap between the Wall and the Handle. (see Fig.2)

NOTE: Extensions may be acquired if correct installation can not be achieved.(Contact manufacturer)

Once the gap from the Wall to the Handle is between 2-3mm, remove the Handle and tighten the Set Screws of the Adjustment Fitting.
 When securing the Handle adjustment Fitting, ensure the Set Screws are tightened onto the flats of the Cartridge Extension. (see Fig.2)
 Do not tighten the Set Screws on the threads of the Cartridge Extension.
 Fit the Handle so the Set Screw is positioned at the bottom.(tighten well)
 Note the Set screw must engage in the groove of the Adjustment Fitting.