

Mizu Soothe Shower Mixer

IMPORTANT NOTE:

Mixer must be installed to the requirements of AS/NZS 3500 by a qualified plumber. Your mixer comes to you already factory assembled and tested. We do not recommend the dismantling of any internal part of the mixer. The mixers are factory tested and sealed so as to give the best performance.

INSTALLATION INSTRUCTIONS:

- 1. Please flush out new pipe work prior to connecting the new mixer.
- 2. During installation protect the exposed surface finish by using the plastic cover provided.
- 3. In a typical installation, the mixer is mounted on a timber/metal noggin and secured using suitable screws through the mounting lugs.

NOTE: Arrow stamped on the outlet must face up towards shower. If the mixer is to be used as a bath mixer, the pipe will need to be looped to go to the bath outlet.

- 4. Connect mixer to hot and cold water supply.
- 5. Connect to bath and shower outlet.
- 6. Pressure check all connections. Leaking joints are not covered by the warranty.
- 7. When the wall is finished (eg. tiling), remove the plastic cover and fit the cover plate and handle.

CLEANING RECOMMENDATIONS:

We recommend the use of soapy water or approved cleaners. This product should not be cleaned with abrasive materials. Damage caused by any improper treatment is not covered by the product warranty. Refer to Warranty Conditions

