

Model RBA8302-340



Materials & Features

Is a pedestal mounted combination station with eye/face wash with stainless steel bowl, ABS plastic eye/face wash spray heads, an in-line strainer and 15mm stay open ball valve with push handle. The shower has a stainless steel showerhead and 25mm stay-open ball valve with pull rod. The unit complies with AS 4775 / ANSI Z358.1 and is provided with a universal identification sign and a waterproof weekly inspection card.

Technical Detail

Max Inlet Pressure:	500 KPa
Inlet:	32mm Female BSP top side inlet
Waste Outlet [face wash]:	32mm Female BSP
Flow Rate:	90 L/min
Min Supply:	25mm [Needs to be hydraulically calculated]
Showerhead Valve:	25mm
Pull Rod:	735mm
Bowl:	300mm diam, Stainless Steel

Installation:

32mm schedule 40 stainless steel pipe, with 117mm floor fixing flange, fixing by other, installation should be in accordance with AS 4775 / ANSI Z358.1 and local authority requirements.

Available Models

RBA8302-340

Combination station, Eye/Face Wash and Showerhead

Related Products

RBA8302-300

Pedestal Mounted Emergency Shower

Important: Installation instructions and current rough-in details should be furnished with each fixture. Do not rough in without certified dimensions. Dimensions are subject to manufacturer's tolerance of +/-10mm.

