

Semi-Hermetic Compressors

Copeland® **Copeland**

Stream Series

The Stream semi-hermetic compressor range comprises innovations such as multi refrigerant capability and CoreSense Diagnostics for advanced protection and preventive maintenance. The standard stream range is suitable for applications using inverter technology for capacity modulation. Sound shell technology makes Stream the quietest compressor on the market for sound critical applications.



Features

- Motor Temp Protection
- Oil Protection
- Missing Phase or Single Phasing Protection
- Low Voltage Protection
- Voltage Imbalance Protection
- Discharge Temperature Protection
- Locked Rotor Protection
- Compressor Power Consumption Measurement
- Modbus® Communication to system controller
- Compressor Asset and Runtime information
- Failure Alarm History
- Status LEDs to indicate the warning, trip and lockout alarms
- Crank Case Heater Control

Cat. No.	Model No.	No of Cyls	Elect. Supply Volts/Phase	Nom. HP	Displ. m³/h	Nominal Capacity kW			Weight kg	Footprint mm
						Med Temp R404A	Med Temp R134a	Low Temp R404A		
2709737	4MF1-13X-AWMD/D	4	415/3	13	62	33.4	18.2	11.4	177	381 x 305
2709738	4MA1-22X-AWMD/D	4	415/3	22	62	33.6	19.1	10.8	178	381 x 305
2709739	4ML1-15X-AWMD/D	4	415/3	15	71	38.7	22.1	13.2	180	381 x 305
2709740	4MH1-25X-AWMD/D	4	415/3	25	71	38.8	21.4	12.5	187	381 x 305
2709741	4MM1-20X-AWMD/D	4	415/3	20	78	42.6	24.7	14.7	182	381 x 305
2709742	4MI1-30X-AWMD/D	4	415/3	30	78	42.8	23.9	13.9	188	381 x 305
2709743	4MT1-22X-AWMD/D	4	415/3	22	88	47.8	27.7	16.5	183	381 x 305
2709744	4MJ1-33X-AWMD/D	4	415/3	33	88	48.0	26.8	16.0	190	381 x 305
2709745	4MU1-25X-AWMD/D	4	415/3	25	99	54.2	31.2	18.7	186	381 x 305
2709746	4MK1-35X-AWMD/D	4	415/3	35	99	54.4	30.1	17.7	202	381 x 305
2709747	6MM1-30X-AWMD/D	6	415/3	30	120	61.8	36.9	21.6	215	381 x 305
2709748	6MI1-40X-AWMD/D	6	415/3	40	120	64.2	35.3	20.3	219	381 x 305
2709749	6MT1-35X-AWMD/D	6	415/3	35	135	70.4	41.3	25.1	221	381 x 305
2709750	6MJ1-45X-AWMD/D	6	415/3	45	135	72.4	40.4	23.6	223	381 x 305
2709751	6MU1-40X-AWMD/D	6	415/3	40	153	79.8	46.3	28.4	225	381 x 305
2709752	6MK1-50X-AWMD/D	6	415/3	50	153	82.1	45.3	26.6	230	381 x 305