

# BASE MKII SHOWER MIXER

## INSTALLATION INSTRUCTIONS

### Note

The installation must comply with requirements of AS/NZS 3500. Mixer must be installed by a licenced plumber.

### Important

Your mixer comes to you already factory assembled and tested. We do not recommend the dismantling of any internal part of the mixer. The mixers are factory tested and sealed so as to give the best possible performance.

### Installation Procedure

1. Please flush out new pipe work prior to connecting the new mixer.
2. This tap is suitable for high pressure where both hot and cold water supply is at 150kPa or above.
3. During installation protect the exposed finish surface by using the plastic cover provided. Please pay attention to the

minimum/maximum depth.

4. In a typical installation, the mixer is mounted on the timber/ metal noggin and secured with screws (not provided).
5. Shower Mixer Outlet must always face up toward the shower. Connect the mixer to hot and cold water supply.
6. Pressure check all connections. Leaking joints are not covered by the warranty.
7. When ready for finishing, remove the plastic cover and assemble cover plate (7) and handle (1-3).

### Service - Replacement of Cartridge.

1. Remove cap (3) and unscrew the grub screw (2).
2. Lift handle (1) and remove the cartridge dome (4).
3. Unscrew lock nut (5) and lift cartridge (6).
4. Replace cartridge, replace lock nut, check for water leaks.
5. Replace dome, coverplate and handle.

## EXPLODED VIEW

Item	Description	Product Code
1-3.	Shower Mixer Handle Complete	9502421
4.	Cartridge Dome	
5.	Cartridge Locking Nut	
6.	Cartridge	9502422
7-9.	Shower Mixer Cover Plate	9502428
10.	Shower Mixer Body	
11.	Protective Cover	
12.	Allen Key	

