

ELECTRIC INSTANTANEOUS WATER HEATERS

Instant delivery & unlimited supply

ONLY USES ENERGY WHEN THERE IS DEMAND FOR HOT WATER


ELWA designs, manufactures and supplies energy-saving products and solutions

Heating water accounts for 25% of energy consumption in homes, so it is important to install an energy efficient water heater. In the long run, this saves a lot of money. ELWA's mission is to provide solutions that are the most energy and water efficient.

ELWA water heaters are compact in size, highly energy efficient and never run out of hot water. The Hotrun water heaters have been manufactured locally by Elwa for 30+ years. Each water heater is quality tested to ensure your access to instant, constant flow of hot water is never compromised.

Elwa Hotrun X water heaters feature metal-casted heat exchangers with high capacities, minimising the risk of leakage. With our Poly-Carbonate casing our water heaters ensure long lasting reliable products.

Unlimited hot water & highly energy efficient The power to the elements in the heat-exchanger are instantly activated as soon as there is demand for hot water. A Hotrun only uses energy when there is demand for hot water. Unlimited supply with almost 100% efficiency.



Committed to a brighter cleaner future

LOW ENERGY CONSUMPTION HIGH PERFORMANCE

Advantages of ELWA Hotrun-X electric instantaneous water heaters:

- Variable power supply selection (kW) to suit every situation
- Single, 2- and 3-phase options
- Programmable temperature limiter
- Digital temperature control
- Touch screen control panel
- Optional LoRa communication for remote diagnostics and service
- Legionella thermal disinfection mode
- The most efficient technology to generate unlimited hot water
- No pressure limiters required

- Energy is only used when there is demand for hot water
- Quiet operation
- The compact size allows for installation anywhere
- Fully electric, no flue, no gas connection required
- No plastics in the water path
- Designed to meet all plumbing standards in Australia & New Zealand
- 10 year product warranty*

The X-series has optional remote monitoring via LoRa. Any possible error can easily be analysed and rectified. The water heater can send the diagnostics directly to a service centre. This saves time (or a service technician) and money (time = money)! LoRa has the option to allow us to calculate the energy and water consumption.



*10 year warranty for products purchased after January 1, 2024 High water pressure will never void the warranty, unlike any other products on the market.

			E WATER HE		
Power (kWatt)	2.8 kW	3.8 kW	4.8 kW	6.0 kW	
or Installer to select Single-Phase power connection	12 Amps	16 Amps	20 Amps	25 Amps	
Performance (at Δ T = 25°C)	Flowrate 1.8 L/min	Flowrate 2.3 L/min	Flowrate 2.8 L/min	Flowrate 3.6 L/min	3)≋ ELWA
No. of Hand Wash Basins	1	1	1	2	
lo. of Kitchenette	I	1	1	1	242 . *
limensions		315 x 204	x 130 mm	· · · · · · · · · · · · · · · · · · ·	27C++
oltage	315 x 204 x 130 mm 1×240 V				XG
P rating			224		۵ ک
Connection	1/2" BSP				
Veight	3 kg				- (
Pressure rating			m 2 MPa		6
н			2-PHASE VVA		1
Power (kWatt)	6.0 kW	7.6 kW	9.6 kW	11 kW	
or Installer to select Single-Phase power connection	1 x 25 Amo	1 x 32 Amos	1 x 40 Ampo	1 x 50 Amos	
0 1	1 x 25 Amps 2 x 12.5 Amps	1 x 32 Amps 2 x 16 Amps	1 x 40 Amps 2 x 20 Amps	1 x 50 Amps 2 x 25 Amps	
wo-Phase power connection Performance (at Δ T = 25°C)	Flowrate 3.6 L/min	Flowrate 5.0 L/min	Flowrate 6.0 L/min	Flowrate 7.0 L/min	
No. of Hand Wash Basins, or	1	2	2 to 3	3	∃)≋ ELWA
lo. of Showers, or	1 *in climate zone 1 & 3	2 1 *in climate zone 1 & 3	1 *in climate zone 1. 2. & 3	1	
No. of Hairdresser Basins, or	1 *in climate zone 1 & 3	1 *in climate zone 1, 2 & 3	1 *in climate zone 1, 2 & 3	1	\$42 _{**}
lo. of Kitchenette, or	1	1 III climate zone 1, z & 3	1	1, *2 in climate zone 1, 2, & 3	HOTRUN
lo. of Kitchen Sinks, or	1 *in climate zone 1, 2 & 3	1 *in climate zone 1, 2, & 3	1 *in climate zone 1, 2, & 3	1, *2 in climate zone 1, 2, & 3	X11 () () ()
limensions				1, 2 in climate zone 1, 2, & 3	
	315 x 204 x 130 mm 1 x 240 V or 2 x 240 V				
/oltage P rating					
Connection	IP24 1/2" BSP				1911 1923
	4 kg				
Veight Pressure rating			m 2 MPa		
	HOTRUN		SE WATER H	EATERS	
			AND WASH BASINS		
	1-3 HAIF	ADRESSER BASINS	and/or 1-3 KITCHE		
Power (kWatt) or Installer to select	12 kW	18	kW	24 kW	
hree-Phase power connection	3 x 16 Amps	3 x 25	Amps	3 x 35 Amps	
Performance (at Δ T = 25°C)	Flowrate 8.0 L/min		11 L/min	Flowrate 14 L/min	⇒ ELWA
Io. of Hand Wash Basins	3		5	7	
lo. of Showers	1			3 in climate zone 1, 2, & 3	HOTRUN
Io. of Hairdresser Basins	1		2	3	X24
lo. of Kitchen Sinks	1		2	3	
Dimensions	480 x 240 x 120 mm				
/oltage	415 V				-
P rating	IP24				Q
Connection	1/2" BSP				
	6 kg				T T
Veight	Maximum 1 Mpa (tested at 2 Mpa)				

For more information and to find the most suitable model for you, please contact us. ELWA BV Amsterdam The Netherlands Phone +31 (0)20 436 1224 www.elwa.nl ELWA Pty Ltd Adelaide Australia Phone +61 (0)8 8377 6666 www.elwa.com.au