



SZ084-4VI 🗷

Scroll compressor, SZ084S4VC

Refrigerant: R134a; R404A; R407C, Segment usage: Air conditioning, Compressor power supply [V/Ph/Hz]: 400/3/50 460/3/60

PRODUCT DETAILS

Gross weight	69.5 kg
Net weight	64 kg
EAN	5702428582902
Approval standard	CE
	UL
Brand technique	Scroll compressor
Capacity control	Fixed speed
Colour	Blue
Compressor power supply [V/Ph/	400/3/50 460/3/60
Hz]	
Configuration code	Single
Connection type	Brazed
Description	SZ084-4
Diameter [mm]	254 mm
Discharge connection height [mm]	465 mm
Discharge connection pipe size [in]	3/4 in
Discharge connection size [in]	3/4 in
Drawing number	8552036b
Economizer	No
Factory HP [bar]	33 bar
Factory LP [bar]	25 bar
Fitting standard	ODF
Frequency [Hz]	50/60
Gauge port HP	None
Gauge port LP	Schrader
Generation code	С
Glass mounting	Threaded
Glass torque [Nm]	50 Nm
GP LP torque [Nm]	15 Nm
High side max pressure (Ps)	34.3 bar
High Side TS Max	150 ℃
High Side TS Min	-35 ℃
High Side Volume	1.1 L
High value of nominal voltage at	400 V
50Hz [V]	
High value of nominal voltage at	460 V
60Hz [V]	
High value of voltage range at 50Hz	440 V
[V]	



	UCT		

PRODUCT DETAILS	
High value of voltage range at 60Hz	506 V
[V]	
IP protection class	IP54 (with cable gland)
Low side max pressure (Ps)	25 bar
Low Side TS Max	54 °C
Low Side TS Min	-35 ℃
Low Side Volume	13 L
Low value of nominal voltage at	380 V
50Hz [V]	
Low value of nominal voltage at	460 V
60Hz [V]	
Low value of voltage range at 50Hz	342 V
[V]	
Low value of voltage range at 60Hz	414 V
[V]	
LRA	86 A
Maximum Operating Current [MOC]	17 A
MCC	17 A
Model number	SZ084S4VC
Motor protection	Internal overload protector
Mounting torque [Nm]	21 Nm
Nominal cooling capacity at 50Hz	17.3 kW
Nominal cooling capacity at 60Hz	22.5 kW
Nominal heating capacity at 50Hz	16.3 kW
Number of starts per hour [Max]	12
Oil charge [L]	3.25 L
Oil equalization	3/8" flare SAE
Oil equalization torque [Nm]	48 Nm
Oil reference	160SZ
Oil type	POE
Packaging height [mm]	596 mm
Packaging length [mm]	470 mm
Packaging weight [Kg]	67 kg
Packaging width [mm]	370 mm
Packing format	Single pack
Packing quantity	1
Phase	3
Power connections	Screw 4.8 mm
Refrigerant	R134a
	R404A
	R407C
Refrigerant charge [kg] [Max]	8.5 kg
Relief valve	None
RLA	12.1 A
Rotational speed at 50Hz [rpm]	2900 rpm
Rotational speed at 60Hz [rpm]	3500 rpm
Segment usage	Air conditioning
Shipped instructions	Installation instructions
Shipped mounting	Mounting kit with grommets, bolts,
	nuts, sleeves and washers
Shipped oil	Initial oil charge
Suction connection height [mm]	142 mm



Suction connection pipe size [in]	1 1/8 in	
Suction connection size [in]	1 1/8 in	
Swept volume [cm3]	114.5 cm ³	
Technology	Scroll	
Test dif [bar] [Max]	24 bar	
Test HP [bar] [Max]	32 bar	
Test LP [bar] [Max]	25 bar	
Torque earth [Nm]	2 Nm	
Torque power [Nm]	3 Nm	
Total height [mm]	508 mm	
Туре	SZ	
Type designation	Compressor	
Viscosity [cP]	32 cP	
Winding resistance for three-	1.74 Ohm	
phase compressors with identical		
windings [Ohm]		

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🖸

Accessories



8156138 🗷

Mounting kit

 $Mounting\ kit\ for\ one-scroll\ compressor,\ including\ 4\ grommets,\ 4\ sleeves,\ 4\ bolts,\ 4\ washers$



8156132 🗷

Gasket, 1-3/4"

Gasket, 1-3/4"



8173230 🗷

T block connector 52 x 57 mm

T block connector 52 x 57 mm



7765005 🗷

Adaptor

Solder sleeve adaptor set (1-3/4" rotolock, 1-1/8" ODF), (1-1/4" rotolock, 3/4" ODF)



7755011 🗷

Acoustic hood for scroll compressor S084-S090-S100

Acoustic hood for scroll compressor S084-S090-S100

For more information, please use this link to visit the product page on Danfoss Product Store 🗷



Accessories



8153004 🗷

Adaptor

Solder sleeve, P02 (1-3/4" rotolock, 1-1/8" ODF)



8156131 🗷

Gasket, 1-1/4"

Gasket, 1-1/4"



8153008 🗷

Adaptor

Solder sleeve, P04 (1-1/4" rotolock, 3/4" ODF)



8156013 🗷

Gasket set, 1-1/4", 1-3/4", 2-1/4", OSG gaskets black and white

Gasket set, 1-1/4", 1-3/4", 2-1/4", OSG gaskets black and white



7750009 🗷

Discharge thermostat kit

Discharge thermostat kit



8156135 🗈

Service kit for terminal box 96 x 115 mm, including 1 cover, 1 clamp

Service kit for terminal box 96 x 115 mm, including 1 cover, 1 clamp

Spare Parts



120Z0039 🗷

Belt type crankcase heater, 65 W, 400 V, CE mark, UL

Belt type crankcase heater, 65 W, 400 V, CE mark, UL



8168029 🗷

Rotolock valve, V04 (1-1/4" rotolock, 3/4" ODF), Service kit

VALVE SETS V04 1 1/4"-3/4"



120Z0361 🗹

Surface sump heater + bottom insulation, 48 W, 24 V, CE mark, UL

Surface sump heater + bottom insulation, 48 W, 24 V, CE mark, UL

For more information, please use this link to visit the product page on Danfoss Product Store 🗷



Spare Parts



8168028 🗷

Rotolock valve, V02 (1-3/4" rotolock, 1-1/8" ODF), Service kit

VALVE SETS V02 1 3/4"-1 1/8"



120Z0380 🗷

Surface sump heater + bottom insulation, 48 W, 230 V, CE mark, UL

Surface sump heater + bottom insulation, 48 W, 230 V, CE mark, UL



120Z0381 ¹²

Surface sump heater + bottom insulation, 48 W, 400 V, CE mark, UL

Surface sump heater + bottom insulation, 48 W, 400 V, CE mark, UL



8156019 🗷

Oil sight glass with gaskets (black and white)

Oil sight glass with gaskets (black and white)



7773117 🗷

Belt type crankcase heater, 65 W, 400 V, CE mark, UL

Belt type crankcase heater, 65 W, 400 V, CE mark, UL



7754023 🗈

POE lubricant, 160SZ, 1-litre can

POE lubricant, 160SZ, 1-litre can



8156129 🗷

Gasket for oil sight glass (white teflon)

Gasket for oil sight glass (white teflon)



120Z0466 ¹²

Belt type crankcase heater, 65 W, 460 V, CE mark, UL

Belt type crankcase heater, 65 W, 460 V, CE mark, UL



7705006 🗷

MCI

Electronic soft start kit, MCI 15 C



7773107 🗷

Belt type crankcase heater, 65 W, 230 V, CE mark, UL

Belt type crankcase heater, 65 W, 230 V, CE mark, UL

For more information, please use this link to visit the product page on Danfoss Product Store 🗷



Spare Parts



7703009 🗷

Valve set

Packing format: Multi pack, Packing quantity: 6



120Z0382 🗷

Surface sump heater + bottom insulation, 48 W, 460 V, CE mark, UL Surface sump heater + bottom insulation, 48 W, 460 V, CE mark, UL