

Open Condensing Units



Tecumseh

L'Unite Hermetique – HTA EVO Series



Low Temperature Applications – R404A/R448A/R452A



Product Code	Model Number	Ambient Temp. °C	Capacity Watts											
			Evaporating Temperature °C											
			R404A				R448A				R452A			
			-30	-25	-20	-15	-30	-25	-20	-15	-30	-25	-20	-15
3507121	EPCL2480Z -XC	30	1936	2500	3124	3799	1733	2307	2961	3690	1667	2141	2679	3297
		32	1847	2395	3000	3655	1650	2210	2848	3559	1595	2058	2578	3172
		38	1582	2081	2630	3222	1403	1921	2510	3167	1373	1808	2278	2806
		43	1364	1822	2324	2863	1201	1683	2232	2846	1179	1596	2031	2506
3507122	EPCL2511Z -XC	30	2876	3732	4692	5745	2568	3434	4429	5549	2723	3589	4567	5648
		32	2746	3579	4511	5533	2447	3292	4262	5355	2592	3434	4385	5436
		38	2359	3120	3969	4898	2086	2868	3766	4779	2201	2973	3842	4802
		43	2040	2740	3519	4370	1789	2518	3357	4304	1880	2591	3392	4277
3507123	EPCL2511Z -XG	30	2662	3463	4364	5360	2376	3182	4113	5166	2521	3330	4248	5269
		32	2543	3321	4197	5164	2264	3051	3959	4987	2400	3187	4080	5073
		38	2186	2898	3696	4575	1931	2659	3500	4453	2040	2761	3577	4485
		43	1891	2546	3280	4086	1657	2336	3121	4013	1743	2408	3161	3998
2709904	EPCL2516Z-3ph	30	3116	4085	5152	6302	2768	3752	4874	6125	2986	3948	5020	6190
		32	2962	3899	4931	6042	2628	3581	4670	5886	2831	3762	4800	5933
		38	2506	3348	4272	5266	2221	3084	4075	5187	2373	3214	4150	5172
		43	2136	2898	3733	4628	1899	2689	3600	4626	2004	2770	3623	4552
2709905	EPCL2522Z-3ph	30	4257	5497	6894	8439	3751	5016	6484	8155	4050	5283	6694	8279
		32	4068	5269	6621	8116	3580	4807	6234	7861	3865	5059	6426	7963
		38	3510	4595	5814	7164	3084	4203	5510	7009	3319	4398	5634	7027
		43	3057	4047	5158	6386	2694	3729	4941	6338	2878	3863	4991	6265

Capacities based on EN13215 Midpoint ratings: Return Vapour 20°C, Subcooling 3K.

Additional Cooling Required