



Mizu Bloc MK2 Shower Mixer Matte Black

IMPORTANT NOTE:

Mixer must be installed to the requirements of AS/NZS 3500 by a qualified plumber. Your mixer comes to you already factory assembled and tested. We do not recommend the dismantling of any internal part of the mixer. The mixers are factory tested and sealed so as to give the best performance.

INSTALLATION INSTRUCTIONS:

1. Please flush out new pipe work prior to connecting the new mixer
2. This tap is suitable for high pressure where both hot and cold water supply is at 150kPa or above
3. During installation protect the exposed finish surface by using the plastic cover provided. Please pay attention to the minimum/maximum depth
4. In a typical installation, the mixer is mounted on the timber/metal noggin and secured with screws (not provided)
5. Shower Mixer Outlet must always face up toward the shower. Connect the mixer to hot and cold water supply
6. Pressure check all connections. Leaking joints are not covered by the warranty.
7. When ready for finishing, remove the plastic cover and assemble

SERVICING - REPLACEMENT OF CARTRIDGE:

1. Remove decorative cover (4) and unscrew the grub screw (3) using an allen key
2. Lift off handle (2) and unscrew the cartridge dome (6), unscrew brass locking nut (7) and lift out cartridge (8)
3. Replace the cartridge (8), replace the brass locking nut (7), replace the cartridge dome (6) and replace handle (2)
4. Tighten grub screw (3) and push in decorative cover (4)

CLEANING RECOMMENDATIONS:

We recommend the use of soapy water or approved cleaners. This product should not be cleaned with abrasive materials. Damage caused by any improper treatment is not covered by the product warranty. Refer to Warranty Conditions