

Open Condensing Units



Tecumseh



L'Unite Hermetique – HTA Condensing Unit

Medium Temperature Applications – R134a



Product Code	Model Number	Ambient Temperature °C	Capacity Watts				
			Evaporating Temperature °C				
			R134a				
			-10	-5	0	5	10
2709829	AET4425YHR-FZ	30	331	419	515	621	734
		32	322	407	501	604	714
		38	293	372	459	552	653
		43	269	342	423	509	602
9507060	AET4430YHR-FZ	30	434	541	662	798	947
		32	422	527	645	777	923
		38	388	484	593	714	849
		43	359	448	549	662	787
9507062	AET4440YHR-FZ	30	555	678	816	968	1133
		32	541	661	795	943	1104
		38	500	610	733	869	1016
		43	465	568	682	807	943
9507061	AET4450YHR-FZ	30	760	929	1120	1331	1562
		32	740	906	1091	1297	1522
		38	680	834	1005	1195	1404
		43	630	774	934	1111	1304
9507063	AET4456YHR-FZ	30	819	999	1198	1418	1657
		32	799	974	1169	1383	1615
		38	736	899	1078	1275	1489
		43	684	836	1002	1185	1383
9507064	AET4460YHR-FZ	30	824	1004	1203	1420	1653
		32	804	980	1173	1384	1612
		38	742	906	1084	1278	1486
		43	689	843	1009	1189	1381
3500005	CAJT4476YHR-FZ-1	30	1116	1410	1747	2128	2555
		32	1079	1367	1696	2069	2486
		38	965	1234	1541	1888	2277
		43	868	1121	1409	1734	2098
3500006	CAJT4492YHR-FZ-3	30	1359	1715	2121	2577	3085
		32	1316	1663	2058	2503	2998
		38	1185	1507	1872	2282	2738
		43	1074	1376	1717	2099	2524
3500007	CAJT4511YHR-FZ-3	30	1754	2178	2654	3180	3754
		32	1703	2117	2581	3093	3652
		38	1547	1931	2359	2831	3346
		43	1414	1774	2172	2611	3089
2709845	TAJT4511YHR-TZ-3	30	1737	2164	2642	3170	3748
		32	1685	2103	2569	3083	3646
		38	1526	1914	2344	2818	3336
		43	1393	1754	2154	2594	3074
3505271	FHT4518NHR-XC	30	2480	3146	3901	4745	5678
		32	2389	3037	3771	4593	5502
		38	2130	2726	3401	4158	4997
		43	1929	2486	3115	3819	4601
3505281	FHT4525NHR-XC	30	3284	4155	5137	6230	7431
		32	3167	4017	4975	6041	7213
		38	2825	3613	4500	5487	6573
		43	2551	3288	4116	5038	6054

Open Condensing Units



Tecumseh



L'Unite Hermetique – HTA Condensing Unit

Medium Temperature Applications – R134a



Product Code	Model Number	Ambient Temperature °C	Capacity Watts				
			Evaporating Temperature °C				
			R134a				
			-10	-5	0	5	10
3505272	FHT4525NHR-XG	30	3383	4270	5266	6373	7589
		32	3259	4126	5099	6180	7368
		38	2899	3704	4608	5613	6718
		43	2611	3367	4214	5156	6192
2709848	TAGT4528YHR-2	30	3144	4348	5726	7250	8892
		32	3041	4213	5555	7041	8642
		38	2734	3808	5044	6414	7892
		43	2477	3470	4617	5892	7267
2709849	TAGT4534YHR-2	30	4062	5353	6822	8434	10156
		32	3928	5186	6617	8188	9867
		38	3528	4684	6002	7451	8999
		43	3194	4265	5490	6837	8277
2709850	TAGT4537YHR-2	30	4602	5994	7576	9308	11148
		32	4451	5806	7347	9034	10827
		38	3994	5240	6659	8214	9866
		43	3614	4768	6087	7532	9066
2709851	TAGT4543YHR-2	30	4881	6408	8204	10218	12396
		32	4720	6208	7958	9920	12042
		38	4239	5606	7218	9027	10982
		43	3837	5105	6603	8284	10099

Capacities based on EN13215 Midpoint ratings: Return Vapour 20°C, Subcooling 3K.