


**MANUFACTURING NOTES:**

1. NOMINAL STACK HEIGHT: 51.0MM
2. ELECTRICAL RATINGS: 240V 10% 50Hz 0.5A
3. ROTATION ANT-CLOCKWISE WHEN VIEWED FROM IMPELLOR END
4. NOMINAL PERFORMANCE @ 240V 50Hz: 28.0 LITRES/MINUTE AT 1200mm HEAD HEIGHT
5. MOTOR SHAFT TO BE STAINLESS STEEL GRADE 303
6. MOTOR MUST BE A FULLY ENCLOSED ELECTRICAL COMPONENT
7. MOTOR INSULATION - CLASS B
8. PROTECTION AGAINST THE INGRESS OF WATER TO BE IP20 OR BETTER
9. VENDOR PROPOSED CHANGES TO BE APPROVED BY CLIMATE TECHNOLOGIES BEFORE IMPLEMENTATION
10. FINAL OTS TO BE APPROVED BY CLIMATE TECHNOLOGIES BEFORE COMMENCING PRODUCTION
11. MOTOR SPECIFICATION TO BE PRINTED ON SIDE OF CASING - INCLUDING: -CURRENT -VOLTAGE -FREQUENCY -INSULATION CLASS -PROTECTION OVERLOAD ("PROT.OIL" TO BE PRINTED ON CASING) -CLIMATE THCHNOLOGIES PART NO.
12. MOTOR SPECIFICATIONS LABEL SIZE MUST BE EQUAL TO OR GREATER THAN 45mm X 10mm BUT NO GREATER THAN 70mm X 95mm

THIRD ANGLE PROJECTION



CUSTOMER APPROVAL:

SIGNED:

DATE:

TYPICAL PERFORMANCE AT 240 VOLTS 50 Hz

MOTOR SPEED	IDLE			LOADED			LOCKED			BREAK	
	R.P.M.	AMP.	WATT	mN.m	R.P.M.	AMP.	WATT	mN.m	AMP.	WATT	mN.m

CUSTOMER:

PART NUMBER:

APPLICATION:

MOTOR WEIGHT:

ENVIRONMENT:

FINISH COLOR:

DRAWN BY:

DATE DRAWN:

NATURA

Bruce.Guo

06-12-16



SHANGHAI JAKEL

PUMP TYPE

DRAWING NUMBER

PUMP

6060805

REV.  
A