

Dura PEX Flex Hose Water Stainless Steel Low-Temp Lead Free









SPECIFICATIONS			
Application	General hot and cold water applications (above ground)		
Features	Female hex rubber cone seal		
Working Pressure	1400 kPa		
Temperature Range	5 deg C to 70 deg C		
Materials	Hose Inner Material - Cross-linked polyethylene (PEX) tube		
	Outer Braid - Stainless Steel		
	End Fittings - DR Brass		
	Ferrules - Lead Free Brass		
Standards	AS/NZS 3499		
Watermark	WMKA20101		

SPECIFICATIONS	
Product Warranty	15 Years
15 QALTY GUARANTE	

Disclaimer: Products in this specification manual must by regulation be installed by licensed and registered trade people. The manufacturer/distributor reserves the right to vary specifications or delete models from their range without prior notification. Dimensions are nominal measurements only. Dimensions and set-outs listed are correct at time of publication however the manufacturer/distributor takes no responsibility for printing errors.

Published 11/11/2024




WaterMark




Dura PEX Flex Hose Water Stainless Steel Low-Temp Lead Free


DIMENSIONS						
Product Code	Product Description	Size (inch)	Length (mm)	Inside Diameter (mm)		
9512534	Dura Pex Flex Hose Water 150mm Stainless Steel Low-Temp Lead Free	1/2	150	12		
9512535	Dura Pex Flex Hose Water 225mm Stainless Steel Low-Temp Lead Free	1/2	225	12		
9512536	Dura Pex Flex Hose Water 300mm Stainless Steel Low-Temp Lead Free	1/2	300	12		
9512537	Dura Pex Flex Hose Water 450mm Stainless Steel Low-Temp Lead Free	1/2	450	12		
9512538	Dura Pex Flex Hose Water 600mm Stainless Steel Low-Temp Lead Free	1/2	600	12		
9512539	Dura Pex Flex Hose Water 1000mm Stainless Steel Low-Temp Lead Free	1/2	1000	12		
9512540	Dura Pex Flex Hose Water 1500mm Stainless Steel Low-Temp Lead Free	1/2	1500	12		
9512541	Dura Pex Flex Hose Water with Elbow 225mm Stainless Steel Low-Temp Lead Free	1/2	225	12		
9512542	Dura Pex Flex Hose Water with Elbow 300mm Stainless Steel Low-Temp Lead Free	1/2	300	12		
9512543	Dura Pex Flex Hose Water with Elbow 450mm Stainless Steel Low-Temp Lead Free	1/2	450	12		
9512544	Dura Pex Flex Hose Water with Elbow 600mm Stainless Steel Low-Temp Lead Free	1/2	600	12		
9512545	Performa Mixer Tap Extension Hose 150mm Stainless Steel Low-Temp Lead Free	1/2	150	12		
9512546	Performa Mixer Tap Extension Hose 250mm Stainless Steel Low-Temp Lead Free	1/2	250	12		
9512547	Performa Mixer Tails Hot & Cold Stainless Steel Low-Temp Lead Free	1/2	300	12		




Dura Pex Flex Hose Water Stainless Steel Low-Temp Lead Free



Performa Mixer Tap Extension Hose Stainless Steel Low-Temp Lead Free



Dura Pex Flex Hose Water with Elbow Stainless Steel Low-Temp Lead Free



Performa Mixer Tails Hot & Cold Stainless Steel Low-Temp Lead Free





Dura PEX Flex Hose Water Stainless Steel Low-Temp Lead Free

INSTALLATION NOTES

- Tighten female hex nuts (with rubber cone seal) to 10Nm torque
- The installer is responsible for ensuring proper installation of the product
- · Ensure that all threads are clean and that seals are undamaged
- · Ensure that there are no leaks after installation
- This product is only to be used on potable water
- Don't install this product directly onto hot water units
- · Don't stretch, twist or excessively bend hose
- · Hoses are designed for applications above ground, accessible and not submerged
- It is recommended to connect to an isolation valve immediately before the hose

