

PRO45

SERIES BOTTOM INLET VALVES



TECHNICAL DATA

Operating Pressure: 8 psi - 250 psi. (0.55 - 17.2 Bar), (55 - 1,723 kPa)

Critical Level: 50mm (2")

Flow Range: 1.5 gpm (6.8 L/min) at 8.0 psi (0.55 Bar), (55 kPa)
to maximum 6.0 gpm (27.3 L/min) at 80+ psi (5.5 Bar) (552 kPa)

Sound Level: 34 dBA

Adjustable Height Range: 230mm - 355mm (9"-14")

Durability: 250,000+ Flushes

FEATURES

Fast refill & ultra quiet design

Adjustable height, bottom mount inlet valve

Proprietary pilot technology provides consistent water level at various pressures

Unique self-cleaning valve design operates from VERY LOW to HIGH pressures

Proven & reliable quality



Reduces water hammer

Harsh water durability

Easy install

Heavy duty brass shank (PRO45B Option)

Enhanced shank body (improved chlorine resistance) (PRO45B Option)

5 year warranty

PRO45



PRO45B



Quality, Craftsmanship, Integrity:
Fluidmaster's® PRO Series is for the hardworking plumbing professional who requires high quality, professional grade products that have been engineered for reliability and durability.



30800 Rancho Viejo Road
San Juan Capistrano, CA 92675
www.Fluidmaster.com

FM91595, GREV1, 08/2016



Fluidmaster Holdings Australia Pty Ltd
5B/100 New Street, Ringwood
Victoria 3134
Ph(03) 88702555 Fax(03) 88702566
Email: Salesau@fluidmaster.com
www.fluidmaster.com.au