



003Z1068 🗷

MSV-F2, DN 250, PN 16, Flange

MSV-F2 DN 250 with test plugs PN16, manual balancing valve

PRODUCT DETAILS

| 354 kg | |
|-------------------------------------|--|
| 323 kg | |
| 5702420079974 | |
| Flange | |
| MSV-F2 DN 250 with test plugs PN16, | |
| manual balancing valve | |
| 150 kPa | |
| | |
| No | |
| 952.3 m³/h | |
| 130 °C | |
| -10 °C | |
| PN 16 | |
| Manual balancing | |
| Yes | |
| Yes | |
| With test plugs | |
| MSV-F2 | |
| Cast iron (EN-GJL-250) | |
| DN 250 | |
| • • • • • • • • • • • • | 323 kg 5702420079974 Flange MSV-F2 DN 250 with test plugs PN16, manual balancing valve 150 kPa No 952.3 m³/h 130 °C -10 °C PN 16 Manual balancing Yes Yes With test plugs MSV-F2 Cast iron (EN-GJL-250) |

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store $\[mathbb{L}\]$

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.