

CLASSIC Washing Machine Taps VCLWM3



Congratulations on your purchase of this high quality product from Voda Plumbingware. Please read the following before installation and retain (along with your receipt) for future reference.

TECHNICAL SPECIFICATIONS


Suitable for All Pressures

Minimum Pressure = 17kPa Maximum operating Pressure = 500kPa* (As per NZ Building Code AS/NZ 3500.1) Maximum operating Temperature = 65 deg. Celsius

For domestic use only.

CONFIGURATION

Mains Pressure systemsInstall as supplied.Unequal Low systemsInstall as supplied.Equal Low systemsInstall as supplied.



INSTALLATION

*FOR PRESSURES EXCEEDING 500kPa INSTALL A PRESSURE REDUCING VALVE. THOROUGHLY FLUSH ALL PIPES TO ELIMINATE ANY REMAINING DIRT AND RESIDUE, AND INSTALL INLINE FILTERS. FAILURE TO DO SO MAY VOID THE WARRANTY. TO BE INSTALLED AS PER THE REQUIREMENTS WITH AS/NZS 3500.

- Before commencing installation, turn off the water supply.
- Cut 15mm screwed tube to allow for a minimum 15mm wall protrusion and install. NB: It is essential to apply either Teflon sealing tape or graphite & hemp around the screwed tube prior to installation
- Turn on the water supply.
- Check for leaks.

WARRANTY

PLEASE CALL US BEFORE REMOVING OR UNDERTAKING ANY REPAIR WORK.

Please refer to our website for warranty information: www.vodaplumbingware.co.nz/warranty

In the unlikely event that this product fails during its warranty period, phone our Customer Service team immediately on 0508 367 366 – as unauthorised removal of the product may void the warranty.

CARE AND MAINTENANCE

SHOULD NOT BE CLEANED WITH ACIDIC, CAUSTIC/ALKALINE, ABRASIVE OR CITRIC CLEANERS.

A soft, damp cloth is recommended for cleaning (Not a Micro fibre cloth). Mild soap solutions can also be used on occasion. See website for full care instructions: **www.vodaplumbingware.co.nz/tapware-care-instructions**/

PROUD PARTNER AND SUPPORTER OF MASTER PLUMBERS, GASFITTERS AND DRAINLAYERS

