

mizu

Mizu Drift Basin Mixer (5*)

IMPORTANT NOTE:

Mixer must be installed to the requirements of AS/NZS 3500 by a qualified plumber. Your mixer comes to you already factory assembled and tested. We do not recommend the dismantling of any internal part of the mixer. The mixers are factory tested and sealed so as to give the best performance.

INSTALLATION INSTRUCTIONS:

1. Flush out new pipe work prior to connecting the new mixer
2. All mixers should be installed with isolating stop cocks (Arco)
3. This tap is suitable for high pressure applications where both hot and cold water supply pressures are at 150kpa or above
4. Place the base washer into position
5. Fit the tap body into the mounting hole making sure that the flexible connectors are firmly tightened into the base of the body
6. Do not use Teflon tape on threads
7. From underneath, apply your washer prior to positioning the horse shoe plate
8. Lock the mixer onto the basin or benchtop by tightening the lock nut

SERVICING - REPLACEMENT OF CARTRIDGE:

1. Remove cap and unscrew the grub screw using an allen key
2. Lift off the handle and remove the cartridge dome, unscrew the brass locking nut and lift out the cartridge
3. Replace the cartridge, replace the locking nut, replace the cartridge dome and replace the handle
4. Tighten grub screw and push in cap

CLEANING RECOMMENDATIONS:

We recommend the use of soapy water or approved cleaners. This product should not be cleaned with abrasive materials. Damage caused by any improper treatment is not covered by the product warranty. Refer to Warranty Conditions