

Ghost™ Access and Internal Mini-Split Condensate Pumps



- · Advanced Pump Diaphragm
- Quiet Variable speed operation
- Discreet Easy to install, Univolt models

Quiet. Discreet. Reliable.



mini-split condensate pumps

| Code | Description | Qty |
|-------|----------------|-----|
| 83798 | Ghost Access | 1 |
| 83799 | Ghost Internal | 1 |



FEATURES

- Advanced Diaphragm Pump Technology
- Quiet Variable speed operation
- Discreet Easy to install, Univolt models
- Reservoir connected directly to OEM drain spout
- Delays bio-growth within the reservoir with biocides of the metallic filter
- · Overflow switch connection
- Thermally protected pump
- · Resettable fuse
- · Kits include all required components
- · Cleanable filters

APPLICATION

Ghost Access minipump is designed for quick and easy surface installation under mini-split evaporator, and offers flexible installation with convenient access for future maintenance.

Ghost Internal minipump is for installation inside casing of minisplit evaporator, above ceiling or inside lineset cover. Concealed to preserve a clean finished appearance.

RECOMMENDED FOR

Mini-split systems, residential or commercial

Capacity

Suction Lift

Sound Level

Max Recommended Head

Maximum Water Temp



11 GPH: 41.6 LPH

@ 39"< 21 db(A); @ 1 M < 21 db(A)

50 ft / 15.2 M

104°F / 40°C

5 ft; 1.52 M

| Capacity | Up to 54,500 BTU/HR or 15.97 kW 15 GPH; 56.7 LPH | |
|----------------------|---|--|
| Max Recommended Head | 50 ft / 15.2 M | |
| Maximum Water Temp | 104°F / 40°C | |
| Suction Lift | 5 ft; 1.52 M | |
| Sound Level | @ 39"< 30 db(A): @ 1 M < 30 db(A) | |



RectorSeal, LLC • 2601 Spenwick Drive, Houston, TX 77055, USA • 800-231-3345 • rectorseal.com RectorSeal Australia Pty Ltd. • PO Box 5266 Brendale, Qld 4500, Australia • 1300 77 2878 • rectorseal.com.au