


Geberit HDPE branch fitting 45°



Example image



CHARACTERISTICS

- UV-resistant

TECHNICAL DATA

Product material

PE-HD

Art. no.	Reece no.	DN	d, ø mm	d1, ø mm	arc °	H cm	X1 cm	X2 cm	X3 cm	K1 max. cm	K2 max. cm	K3 max. cm
360.109.16.1	1431068	40, 40	40	40	45	13.5	4.5	9	9	2.5	3	3
361.109.16.1	1433163	50, 40	50	40	45	16.5	5.5	11	11	4	4.5	4.5
361.112.16.1	1430278	50, 50	50	50	45	16.5	5.5	11	11	3.5	2	2
363.115.16.1	1430280	56, 56	56	56	45	18	6	12	12	4	2.5	2.5
364.112.16.1	1430282	60, 50	63	50	45	19.5	6.5	13	13	5	3	3
364.115.16.1	1430283	60, 56	63	56	45	19.5	6.5	13	13	4.5	2.5	2.5
364.120.16.1	1430284	60, 60	63	63	45	19.5	6.5	13	13	4	2	2

<i>Art. no.</i>	<i>Reece no.</i>	<i>DN</i>	<i>d, ø mm</i>	<i>d1, ø mm</i>	<i>arc °</i>	<i>H cm</i>	<i>X1 cm</i>	<i>X2 cm</i>	<i>X3 cm</i>	<i>K1 max. cm</i>	<i>K2 max. cm</i>	<i>K3 max. cm</i>
365.109.16.1	1433197	70, 40	75	40	45	21	7	14	14	6.5	5	6
365.112.16.1	1430285	70, 50	75	50	45	21	7	14	14	6	3	4
365.115.16.1	1430286	70, 56	75	56	45	21	7	14	14	5.5	2.5	3.5
365.120.16.1	1433198	70, 60	75	63	45	21	7	14	14	4.5	2.5	3.5
365.125.16.1	1430288	70, 70	75	75	45	21	7	14	14	4	2.5	2.5
366.109.16.1	1433571	90, 40	90	40	45	24	8	16	16	7.5	5.5	6.5
366.112.16.1	1430251	90, 50	90	50	45	24	8	16	16	8	4	5
366.115.16.1	1430252	90, 56	90	56	45	24	8	16	16	7.5	3.5	4.5
366.120.16.1	1431064	90, 60	90	63	45	24	8	16	16	7	3	4
366.125.16.1	1430254	90, 70	90	75	45	24	8	16	16	6.5	3	3.5
366.130.16.1	1430289	90, 90	90	90	45	24	8	16	16	5	2	2
367.109.16.1	1433582	100, 40	110	40	45	27	9	18	18	9.5	6	7.5
367.112.16.1	1430256	100, 50	110	50	45	27	9	18	18	9.5	5	5.5

<i>Art. no.</i>	<i>Reece no.</i>	<i>DN</i>	<i>d, ø mm</i>	<i>d1, ø mm</i>	<i>arc °</i>	<i>H cm</i>	<i>X1 cm</i>	<i>X2 cm</i>	<i>X3 cm</i>	<i>K1 max. cm</i>	<i>K2 max. cm</i>	<i>K3 max. cm</i>
367.115.16.1	1430290	100, 56	110	56	45	27	9	18	18	9	4	4.5
367.120.16.1	1430291	100, 60	110	63	45	27	9	18	18	8.5	3.5	4
367.125.16.1	1430257	100, 70	110	75	45	27	9	18	18	7.5	3	3.5
367.130.16.1	1430258	100, 90	110	90	45	27	9	18	18	6.5	2.5	3
367.135.16.1	1430292	100, 100	110	110	45	27	9	18	18	5.5	2	2
368.120.16.1	1430266	125, 60	125	63	45	30	10	20	20	10.5	4.5	6
368.125.16.1	1430267	125, 70	125	75	45	30	10	20	20	9.5	4	5
368.130.16.1	1430268	125, 90	125	90	45	30	10	20	20	8.5	3	3.5
368.135.16.1	1430269	125, 100	125	110	45	30	10	20	20	7	2.5	2.5
368.139.16.1	1430270	125, 125	125	125	45	30	10	20	20	6	2	2
369.125.16.1	1430271	150, 70	160	75	45	37.5	12.5	25	25	13.5	6.5	7.5
369.130.16.1	1430274	150, 90	160	90	45	37.5	12.5	25	25	12.5	5.5	6.5
369.135.16.1	1430294	150, 100	160	110	45	37.5	12.5	25	25	11	4.5	5.5

<i>Art. no.</i>	<i>Reece no.</i>	<i>DN</i>	<i>d, ø mm</i>	<i>d1, ø mm</i>	<i>arc °</i>	<i>H cm</i>	<i>X1 cm</i>	<i>X2 cm</i>	<i>X3 cm</i>	<i>K1 max. cm</i>	<i>K2 max. cm</i>	<i>K3 max. cm</i>
369.139.16.1	1430272	150, 125	160	125	45	37.5	12.5	25	25	10	4	5
369.145.16.1	1430273	150, 150	160	160	45	37.5	12.5	25	25	7.5	2.5	2.5
370.135.16.1	1430295	200, 100	200	110	45	54	18	36	36	7.5	10	0
370.139.16.1	1430300	200, 125	200	125	45	54	18	36	36	5.5	9	0
370.145.16.1	1430296	200, 150	200	160	45	54	18	36	36	4	5.5	0
370.146.16.1	1430301	200, 200	200	200	45	54	18	36	36	0	0	0
371.135.16.1	1430302	250, 100	250	110	45	66	22	44	44	14	10	7.5
371.139.16.1	1430303	250, 125	250	125	45	66	22	44	44	13	13	6.5
371.145.16.1	1430297	250, 150	250	160	45	66	22	44	44	10.5	10	0
371.146.16.1	1430304	250, 200	250	200	45	66	22	44	44	7.5	0	1.5
371.147.16.1	1430298	250, 250	250	250	45	66	22	44	44	4	0	0
372.135.16.1	1431120	300, 100	315	110	45	84	28	56	56	23	20	16
372.145.16.1	1430306	300, 150	315	160	45	84	28	56	56	19.5	17.5	12.5

<i>Art. no.</i>	<i>Reece no.</i>	<i>DN</i>	<i>d, ø</i> mm	<i>d1, ø</i> mm	<i>arc</i> °	<i>H</i> cm	<i>X1</i> cm	<i>X2</i> cm	<i>X3</i> cm	<i>K1 max.</i> cm	<i>K2 max.</i> cm	<i>K3 max.</i> cm
372.146.16.1	1430307	300, 200	315	200	45	84	28	56	56	16.5	5	10
372.147.16.1	1430308	300, 250	315	250	45	84	28	56	56	13	5.5	6.5
372.148.16.1	1430309	300, 300	315	315	45	84	28	56	56	8.5	2	2