



003Z0645 🗷

ASV-PV 3G, DN 100, 60 kPa - 100 kPa, Flange

ASV-PV DN 100, 60-100 kPa, automatic balancing valve

PRODUCT DETAILS

Gross weight	65.4 kg	
Net weight	65.4 kg	
EAN	5702421558638	
Connection types	Flange	
Description	ASV-PV DN 100, 60-100 kPa, automatic	
	balancing valve	
Differential pressure over the valve	250 kPa	
[kPa] [Max]		
Differential pressure setting [kPa]	100 kPa	
[Max]		
Differential pressure setting [kPa]	60 kPa	
[Min]		
Factory setting [kPa]	80 kPa	
Impulse tube length [m]	2.5 m	
Kvs values [m³/h]	76 m³/h	
Media temperature [°C] [Max]	120 °C	
Media temperature [°C] [Min]	-10 °C	
Mounting position	Return pipe	
Pressure class	PN 16	
Product group	Automatic balancing	
Shut-off function	Yes	
Туре	ASV-PV 3G	
Valve body material	Grey cast iron (EN-GJL-250)	
Valve size	DN 100	

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🗷

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.