

**195B0640****Reciprocating compressor, SC21CL**

This product is not available in this store. Please contact your local Customer Service Center.

[Customer Service Center](#)

Refrigerant: R404A, Segment usage: Refrigeration LT, Compressor power supply [V/Ph/Hz]: 220-240/1/50

PRODUCT DETAILS

Gross weight	15.18 kg
Net weight	15 kg
Application energy level	Standard LBP
Applications	LBP
Auxiliary winding resistance (start winding) for single-phase compressors alt [Ohm]	13.6 Ohm
Base plate type	Universal
Brand technique	Reciprocating compressor
Capacity control	Fixed speed
Colour	Black
Compressor power supply [V/Ph/Hz]	220-240/1/50
Configuration code	Single
Cut in current HST [A]	23.6 A
Description	SC21CL
Discharge connection angle [°]	37°
Discharge connection comments	Rubber plug
Discharge connection diameter [mm]	6.2 mm
Discharge connection height [mm]	100 mm
Discharge connection material	Copper
Economizer	No
Free gas volume [cm³]	1410 cm ³
Frequency [Hz]	50
Height from baseplate [mm]	203 mm
High value of nominal voltage at 50Hz [V]	240 V
High value of voltage range at 50Hz [V]	255 V
Length [mm]	255 mm
Liquid injection	No
Low value of nominal voltage at 50Hz [V]	220 V
Low value of voltage range at 50Hz [V]	187 V
LRA HST 60Hz [A]	23.6 A
LRA HST [A]	23.6 A

Product Detail | Reciprocating compressor, SC21CL

PRODUCT DETAILS

Main winding resistance for single-phase compressors [Ohm]	3.3 Ohm
Model number	SC21CL
Motor type	CSR
No. of phases (compressor)	1
Oil quantity [cm ³]	550 cm ³
Oil type	POE
Packing format	Single pack
Packing quantity	1
Process connection angle [°]	37 °
Process connection comments	Rubber plug
Process connection diameter [mm]	6.2 mm
Process connection height [mm]	183 mm
Process connection material	Copper
Refrigerant	R404A
Refrigerant charge [kg] [Max]	1.3 kg
RLA	4.00 A
Rotational speed at 50Hz [rpm]	3000 rpm
Run capacitor capacitance	10 µF
Segment usage	Refrigeration LT
Speed Platform	Fixed-speed
Start capacitor capacitance	80 µF
Suction connection angle [°]	37 °
Suction connection comments	Rubber plug
Suction connection diameter [mm]	10.2 mm
Suction connection height [mm]	183 mm
Suction connection material	Copper
Swept volume [cm ³]	20.95 cm ³
Technology	Reciprocating
Total height [mm]	209 mm
Type	SC
Type designation	Compressor
Voltage 50Hz [V]	220 V
Voltage 50Hz [V] [Max]	240 V
Width [mm]	151 mm
Winding temperature short term [°C] [Max]	135 °C
Winding temperature stat [°C] [Max]	125 °C

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)