.P





www.kadenair.com.au

## Kaden Ducted Air Conditioners.

#### Creating the ideal climate in different rooms throughout your home is essential for your family's comfort.

Whether it's a sweltering summer day or an icy winter morning, Kaden ducted air conditioners allow you to regulate your home's temperature effortlessly. This makes it the air conditioner for all seasons. Designed specifically for Australian conditions, these units deliver enduring performance matched with whisper quiet operation. Made to last, every Kaden ducted air conditioner comes with a full 5-year domestic warranty. All of these features make Kaden the perfect choice for versatile living.



## Features at a glance

### Your comfort zone

The Kaden Ducted Air Conditioner offers the ideal heating and cooling solution for your home. Incorporating the latest technology, the KDI series provides quiet operation in any environment, and is specifically designed to moderate the Australian climate.



# Gold fin protection An anti-corrosive gold nano-coating that prevents bacteria breeding and improves heat transfer.

### Active clean

Your KDI automatically washes away contaminants by freezing and thawing the frost on the heat exchanger, preventing mould and excess moisture buildup.

Eco mode

efficient system.

Built for the energy-conscious, ECO mode reduces energy consumption by up to 60% compared to normal operation

and lasts for 8 hours for a truly

## **Kaden Splittable** Design



### **Splittable Design**

With a split design structure, the indoor KDI60 unit can be easily separated into two and then reassembled within the ceiling making installation and maintenance a breeze.





#### Once in ceiling, reassemble unit



## Simple to install.

Ease of installation is a hallmark of all Kaden units. Our ducted units are designed to make the installer's job simple and straightforward. Available in 7.3kW, 10.5kW, 12.5kW, 14kW and 17kW, there is a size to suit any home.





7.3kW

10.5kW-17.0kW





7.3kW-10.5kW

12.5kW-17.0kW

#### **Product specifications**

			KDI24- 7.3kW	KDI36 - 10.5kW	KDI42 - 12.5kW	KDI48 - 14.0kW	KDI60 - 17.0kW		
Power supply	PH - V - Hz			1 Phase, 220-240V, 50Hz					
Rated current		A	16	21	31	31	31		
Running current	Cooling / Heating	A	9.8/7.9	14.2/12.8	18.2/16.3	18.2/16.3	22.5/19.5		
Recommended circuit breaker*		A	25	32	40	40	40		
Capacity	Cooling (Range)	kW	7.3 (2.4-9.0)	10.5 (3.2-11.9)	12.5 (4.20-15.75)	14.0 (4.2-15.8)	17.0 (6.8-19.5)		
	Heating (Range)	kW	7.5 (1.8-10.5)	11.5 (3.5-13.5)	13.0 (4.4-16.7)	14.5 (4.4-16.7)	18.0 (29.3-21.1)		
Input	Cooling (Range)	kW	2.1 (5.37-2.9)	3.1 (0.6-3.9)	3.7 (1.0-6.5)	4.2 (1.0-6.5)	5.3 (1.1-6.5)		
	Heating (Range)	kW	1.8 (0.4-3.0)	2.7 (0.5-3.3)	3.2 (0.5-5.3)	3.6 (0.5-5.3)	4.6 (0.6-5.0)		
Star rating: Hot / Average / Cold	Cooling		5/4/4.5	5.5/4.0/4.5	4/3.5/3.5	4/3.5/4	4.5/3.5/3.5		
	Heating		3.0/2.5/2.0	3.0/2.5/2.5	3.0/2.5/2.0	3.5/2.5/2.0	3.5/2.5/2.0		
EER	Cooling		3.48	3.39	3.43	3.33	3.24		
COP	Heating		4.17	4.26	4.13	4.03	3.96		
Sound power level	Outdoor	dBA	65	68	70	71	72		
Sound pressure level (Low, Med, Hi)	Indoor	dBA	34.5/37/39	40/43.5/46.5	40/43.5/46.5	40/43.5/46.5	45.3/49.5/53		
Airflow (Low, Med, Hi)		l/sec	290/361/416	333/487/655	397/665/859	397/665/859	635/833/1056		
External dimensions (H x W x D)	Indoor	mm	249 × 1100 × 774	380 × 1200 × 625	380 × 1200 × 625	380 × 1200 × 625	440 × 1400 × 858		
	Outdoor	mm	673 × 890 × 342	810 × 946 × 410	1333 × 952 × 415	1333 × 952 × 415	1333 × 952 × 415		
Net/ Gross weight	Indoor	kg	31.6/38.3	54.0/62.0	53.3/61.6	53.3/61.6	81.1/91.6		
	Outdoor	kg	45.0/47.8	70.1/74.5	95.1/109.2	95.1/109.2	95.8/110.0		
Refrigerant piping	Liquid line	mm (inch)	Ø9.52 (3/8")	Ø9.52 (3/8")	Ø9.52 (3/8")	Ø9.52 (3/8")	Ø9.52 (3/8")		
	Gas line	mm (inch)	Ø15.90 (5/8")	Ø15.90 (5/8")	Ø15.90 (5/8")	Ø15.90 (5/8")	Ø19.0 (3/4")		
	Connection method		Flare connection	Flare connection	Flare connection	Flare connection	Flare connection		
Refrigerant	Туре			R32					
	Quantity	kg	1.75	2.6	3.6	3.6	4.0		
	Pre charged to pipe length	m	20	20	20	20	20		
Max pipe length		m	50	75	75	75	75		
Max height difference		m	25	30	30	30	30		
Operation range	Cooling	°C		0 to 50					
	Heating	°C		-15 to 30					

\* Recommendations are a guide only. Circuit breaker and electrical safety equipment must be installed to relevant standards and regulations by a qualified licensed electrician

**Ultimate Control** 

## **Indoor Unit Feature Comparison**

Features	KDI24	KDI36	KDI42	KDI48	KDI60
Manual external static pressure setting	~	~	~	~	~
Automatic external static pressure setting	~	~	v	~	~
Wired controller	~	~	~	~	~
Wi-Fi control	~	~	~	~	~
Automatic fan speed	<ul> <li>✓</li> </ul>				
Outside air intake	<ul> <li>✓</li> </ul>	×	×	×	×
Filter	<ul> <li>✓</li> </ul>				
Self diagnostics	<ul> <li>✓</li> </ul>	<ul> <li>✓</li> </ul>	v	<ul> <li>✓</li> </ul>	<ul> <li>✓</li> </ul>
Splittable indoor unit	×	×	×	×	<ul> <li>✓</li> </ul>
Built in drain pump	<ul> <li>✓</li> </ul>				
Turbo mode	<ul> <li>✓</li> </ul>	<ul> <li>✓</li> </ul>	v	<ul> <li>✓</li> </ul>	<ul> <li>✓</li> </ul>
Automatic operation	<ul> <li>✓</li> </ul>	<ul> <li>✓</li> </ul>	v	<ul> <li>✓</li> </ul>	<ul> <li>✓</li> </ul>
Weekly timer	<ul> <li>✓</li> </ul>				
Low profile bulkhead design	<ul> <li>✓</li> </ul>	×	×	×	×
Auto restart function	<ul> <li>✓</li> </ul>				
Independent dehumidification	~	<ul> <li>✓</li> </ul>	~	<ul> <li>✓</li> </ul>	<ul> <li>✓</li> </ul>
Clean air function	<ul> <li>✓</li> </ul>	<ul> <li>✓</li> </ul>	~	<ul> <li>✓</li> </ul>	<ul> <li>✓</li> </ul>
DR function	~	<ul> <li>✓</li> </ul>	<ul> <li>✓</li> </ul>	~	<ul> <li>✓</li> </ul>



### Wired controller

Standard with every system

117

### Easy to read backlit display

A simple controller display that's easy to read day or night.

#### Weekly timer schedule

Set your on temperature for work days then off on weekends.





works with the Google Assistant amazon alexa

### Peace of mind.

#### Warranty

Kaden is committed to total customer care, so you'll enjoy market-leading warranties and ongoing after-sales support. The Kaden range offers a 5 year warranty on parts and labour for residential and light commercial.



Residential & Commercial Parts & labour

Non-human comfort Parts & labour





For more information go to kadenair.com.au

Due to limitations in the printing process the colours in this brochure are a guide only. The manufacturer/distributor reserves the right to vary specifications or delete models from their range without prior notification. The manufacturer/distributor takes no responsibility for printing errors. All products enjoy a product replacement warranty. For full warranty details visit www.kadenair.com.au V1 [BROCHURE CODE 2111103]

metalflex ACTROL F