

FINAL INSPECTED MOTORS MUST COMPLY WITH ELECTRIC MOTOR VIBRATION SPECIFICATION (ES049)

THIRD ANGLE PROJECTION.

Q.R. No.		6735		CUSTOMER NO.		-		
CUSTOMER		-						
MOTOR RATING	VOLTS	240	Hz	50	Ph	1	Duty	A.O.M.
	RPM.	1370			1.1			AMPS
	NOM. OUTPUT	100 WATTS						
ROTATION		ANTICLOCK WISE AT LEAD END						
CAPACITOR		START	-----	µF/V	RUN	2/440		µF/V
ENCLOSURE		FULLY VENTED ENDSHIELDS						
MOTOR TYPE		CSR			INSULATION CLASS		B 130	
THERMAL PROTECTION		AUTO RESET OVERLOAD						
APPLICATION		BLOWER						
BEARING D.E.		6202ZZ			LUBRICATION		LONG LIFE, WIDE RANGE	
BEARING N.D.E.		6202ZZ						
SUPPLY LEAD		SINGLE CORE1440 ±30 BRAIDED SLEEVING						
EARTH PROVISION		VIA SUPPLY LEAD						
BASIC BUILD SPECIFICATION		305-570-02			PAINT/ COLOUR		PC GREY CASE PLAIN E/SHIELDS	
PERFORMANCE SPECIFICATION		SP85078-01						
CONNECTION DIAGRAM		393-402-01			RATING LABEL		SSTDAUTO.FMT	

