



082G5410 🗷

AMZ 112, 156.00 m³/h, Rp 1 1/2 AMZ 112 ON/OFF 2-w int th 230V DN40

PRODUCT DETAILS

I NODOCI DEIAILS		
Gross weight	1.96 kg	
Net weight	1.95 kg	
EAN	5710104079905	
Application	Domestic and commercial central	
	heating	
Application alternative VSP	Solar energy plants	
Closing differential pressure	6 bar	
(diverting) [bar] [Max]		
Closing differential pressure	6 bar	
(mixing) [bar] [Max]		
Connection size	Rp 1 1/2	
Connection types	Internal thread	
Description	AMZ 112 ON/OFF 2-w int th 230V	
	DN40	
Diameter [mm]	40 mm	_
Kvs values [m³/h]	156 m³/h	_
Media temperature [°C] [Max]	110 ℃	
Media temperature [°C] [Min]	2 °C	
Medium alternative	Drinking water	
Medium alternative 2	Glycolic water up to 50%	
Mounting version	Free	
Number of ports	2	
Operating torque [Nm]	10 Nm	
Permissible media	District heating/cooling circulation	
	water	
Pressure nominal [bar]	25 bar	
Product group	Motorized control valves	
Spindle position	None	
Туре	AMZ 112	
Valve ball material	CW 614 N UNI EN 12164	
Valve body material	CW 617 N UNI EN 12165	
Valve stem material	CW 614 N UNI EN 12164	

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🗷

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.