



COOL-FIT 4.0 Reducer, d250-d450

Model:

- Pre-insulated PE100 SDR 17 metric
- Insulation made from GF HE foam
- Outer jacket impact resistant. Color: black
- B: Spigot Fitting with free end (separate electrofusion fitting needed for joining)

d/D (mm)	d1/D1 (mm)	PN	Code	Weight (kg)	L (mm)	L1 (mm)	z (mm)	Type
250/355	225/315	PN 10	738 903 825	2.800	123	110	332	B
280/400	225/315	PN 10	738 903 829	4.700	126	110	335	B
280/400	250/355	PN 10	738 903 830	5.100	133	110	365	B
315/450	225/315	PN 10	738 903 836	7.100	126	110	340	B
315/450	250/355	PN 10	738 903 837	7.400	133	123	365	B
315/450	280/400	PN 10	738 903 838	6.800	133	126	365	B
355/500	250/355	PN 10	738 903 844	8.200	148	123	390	B
355/500	280/400	PN 10	738 903 845	7.700	148	126	390	B
355/500	315/450	PN 10	738 903 846	8.300	148	133	390	B
400/560	280/400	PN 10	738 903 853	9.100	150	126	415	B
400/560	315/450	PN 10	738 903 854	11.400	150	133	420	B
400/560	355/500	PN 10	738 903 855	11.000	150	148	405	B
450/630	280/400	PN 10	738 903 862	13.200	165	126	390	B
450/630	315/450	PN 10	738 903 863	13.600	165	133	390	B
450/630	355/500	PN 10	738 903 864	13.700	165	148	393	B
450/630	400/560	PN 10	738 903 865	14.800	165	150	395	B

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>