

Induced Draft Evaporators



Cabero

CH – Air Defrost Evaporators 300-350mm Fans

Standard Product Code	Cabero Pro Product Code	Model	Capacity @ -4°C SST & 6 KTD Watts – MID POINT						
			R404A	R452A	R448A	R449A	R134a	R450A	R513A
2710355	3511000	CH4B1/30-1	1497	1407	1437	1422	1362	1332	1377
2710356	3511001	CH4C1/30-1	1855	1678	1714	1696	1624	1589	1642
2710357	3511002	CH4B1/35-1	2385	2187	2233	2210	2117	2071	2140
2710358	3511003	CH4C1/35-1	2985	2810	2870	2840	2720	2660	2750
2710359	3511004	CH4B2/30-1	2993	2857	2918	2888	2766	2705	2797
2710360	3511005	CH4D1/35-1	3512	3203	3271	3237	3101	3032	3135
2710361	3511006	CH4C2/30-1	3709	3479	3553	3516	3368	3294	3405
		CH4E1/35-1	3920	3625	3702	3663	3509	3432	3548
2710362	3511007	CH4B2/35-1	4769	4584	4682	4633	4438	4340	4486
2710363	3511008	CH4C2/35-1	5969	5683	5804	5743	5501	5380	5562
2710364	3511009	CH4D2/35-1	7025	6580	6720	6650	6370	6230	6440
2710365	3511010	CH4E2/35-1	7839	7352	7509	7430	7117	6961	7196
2710366	3511011	CH4C3/35-1	8954	8558	8740	8649	8285	8103	8376
2710367	3511012	CH4D3/35-1	10537	9933	10145	10039	9616	9405	9722
2710368	3511013	CH4E3/35-1	11759	11054	11289	11172	10701	10466	10819
2710369	3511014	CH4D4/35-1	13840	13236	13518	13377	12814	12532	12954
2710370	3511015	CH4E4/35-1	15688	14689	15002	14846	14221	13908	14377

Capacities based on EN328 Midpoint ratings SC2: Air inlet temp 2°C, Evaporating temp -4°C, 6K TD.