

Hotrun X24



Can serve multiple Handwash Basins, Showers and Kitchen Sinks simultaneously

3-Phase power connection (no neutral required)

Dimensions	480 x 240 x 120 mm		
Power rating	12 kW / 18 kW / 24 kW		
Voltage	415 V		
Current	3 x 16 / 3 x 25 / 3 x 35 Amps		
IP rating	IP24		
Connection	1/2" BSP		
Weight	6 kg		
Performance (at $\Delta T = 25^{\circ}\text{C}$) (Voltage needs to be 415V)	Set to 12 kW	Flowrate 8 L/min	415V-3x16Amps
	Set to 18 kW	Flowrate 11 L/min	415V-3x25Amps
	Set to 24 kW	Flowrate 14 L/min	415V-3x35Amps
Inlet pressure rating	1 Mpa (tested at 2 MPa)		

Variable programmable temperature limiter can be set to any required temperature

Variable temperature set-point by the end user (below limiter temperature)

Tip: Base your model selection on the Winter inlet water temperature

Tip: Position within 6 metres of outlet if possible to minimise legionella risk in downstream hot water pipework

Tip: Allow 100mm on sides for cord etc and >100mm under the top & bottom for water connections



Features

1. No noise operation
2. Variable power supply selection (kW)
3. Highly energy efficient and will only use the exact amount of power required
4. Built in temperature limiter
5. Digital display and temperature control
6. Remote life time monitoring option for reporting and full diagnostics
7. Full diagnostics in display
8. Can be installed anywhere
9. 10 Year product warranty