




Example image



CHARACTERISTICS

- Can be welded on both sides with electrofusion coupling
- UV-resistant

TECHNICAL DATA

Product material PE-HD

Art. no.	Reece no.	DN	d, ø mm	arc °	X cm	K cm
360.045.16.1	1430100	40	40	45	4	2
361.045.16.1	1430101	50	50	45	4.5	2
363.045.16.1	1430102	56	56	45	4.5	2
364.045.16.1	1430103	60	63	45	5	2
365.045.16.1	1430104	70	75	45	5	2
366.045.16.1	1430105	90	90	45	5.5	2
367.045.16.1	1430106	100	110	45	6	2.5

<i>Art. no.</i>	<i>Reece no.</i>	<i>DN</i>	<i>d, ø mm</i>	<i>arc °</i>	<i>X cm</i>	<i>K cm</i>
368.045.16.1	1430107	125	125	45	6.5	2.5
369.045.16.1	1430108	150	160	45	6.9	2
370.045.16.1	1430109	200	200	45	18	2.5
361.088.16.1	1430240	50	50	88.5	6	2
363.088.16.1	1430241	56	56	88.5	6.5	2
364.088.16.1	1430242	60	63	88.5	7	2
365.088.16.1	1430243	70	75	88.5	7.5	2
366.088.16.1	1430244	90	90	88.5	8	2
367.088.16.1	1430245	100	110	88.5	9.5	2.5
369.088.16.1	1430246	150	160	88.5	12	2.5