

Product Specification Information

Sizes

>B< Press: 15mm, 20mm, 25mm, 32mm, 40mm, 50mm
 >B< Press XL: 65mm, 80mm, 100mm

Performance

Maximum pressure: 1600kPa
 Temperature range: -35°C to +110°C

Applications

Refer to >B< Press technical guide for suitable applications, or contact support@conexbanninger.com.au to confirm compatibility



Product Specification

A – Specification Statement

Fittings for Copper Tube

Conex Bänninger >B< Press Water 3-point press fittings shall be installed and tested by a licenced plumber following the manufacturer's installation instructions and according to AS/NZS 3500. 15-50mm fittings shall include lead-in edge seal protection and be manufactured with an in-built leak before press O-ring indicator. 65-100mm fittings shall have a triple point seal and stainless steel grip ring. The fittings shall have a maximum working pressure of 1600kPa between temperatures of -35°C to +110°C. Factory fitted elastomeric seals shall be made of black EPDM material. The fitting joints shall be made with pressing tools and jaw sets recommended and approved by Conex Bänninger. Installer training and advice should be requested at www.conexbanninger.com.au

C – Summary Specification

Fittings for Copper Tube

Copper press fittings shall be 15-50mm Conex Bänninger >B< Press 3-point press with black EPDM O-ring and 65-100mm Conex Bänninger >B< Press XL with black EPDM triple point seal. The fittings shall be installed and tested by a licenced plumber following the manufacturer's installation instructions and according to AS/NZS 3500. Installer training and advice should be requested at www.conexbanninger.com.au

B – Product Specification Points

Fittings for Copper Tube

- Fittings shall comply with AS 3688:2016 and be approved by WaterMark certification
- Copper press fittings shall be compatible with Type A and Type B round copper tubes made in accordance with AS 1432 for water in sanitary and heating applications
- Conex Bänninger >B< Press Water 3-point press fittings shall be installed and tested by a licenced plumber following the manufacturer's installation instructions and according to AS/NZS 3500
- Fittings shall have a maximum working pressure of 1600kPa between temperatures of -35°C to +110°C
- Factory fitted elastomeric seals shall be made of black EPDM material.
- 15-50mm fittings shall include lead-in edge seal protection and be manufactured with an in-built leak before press O-ring indicator
- 65-100mm fittings shall have a black EPDM triple point seal and stainless steel grip ring
- The fitting joints shall be made with pressing tools and jaw sets recommended and approved by Conex Bänninger
- Installer training and advice should be requested at www.conexbanninger.com.au