



Bridgland Overwrap Tape



9507251
Bridgland Overwrap Tape
100mm x 30mtr



9507252
Bridgland Overwrap Tape
150mm x 30mtr

SPECIFICATIONS		
Colour	Value:	Black
Weight	Test Method:	ASTM D751
	Value:	245 ± 25 g/m ² (Average)
Elongation at Break	Test Method:	ASTM D1000
	Value:	180 ± 40% (Average)
Thickness	Test Method:	ASTM D751
	Value:	0.19mm (Average)
Break Strength	Test Method:	ASTM D1000
	Value:	3.0 ± 0.6 N/mm
Breakdown Voltage	Test Method:	ASTM D149
	Value:	>16 kV (55% Overlap)
Application Temperature	Value:	0 to +60°C
Service Temperature	Value:	-20 to 60°C
Maximum Temperature	Value:	+75°C
Product Packaging: 9507251	Width:	100mm
	Length:	30m
	Carton Qty:	18 rolls
	Colour:	Black
Product Packaging: 9507252	Width:	150mm
	Length:	30m
	Carton Qty:	12 rolls
	Colour:	Black

Product Description

Bridgland Overwrap Tape is an integral component of the Bridgland System. Bridgland Overwrap Tape is based upon a stabilised and plasticised PVC Film coated with a pressure sensitive natural rubber based adhesive.

Product Characteristics

- Bridgland Overwrap Tape exhibits wide ranging resistance to acids, alkalis, and salts.
- Bridgland Overwrap Tape will afford increased mechanical and dielectric strength when applied over Bridgland Petrolatum Tape.

Product Uses

- Pipeline:** Mechanical, sealing and water proofing of metal above or below ground.
- Other:** Duct sealing, duct jointing, electricians tape, temporary leak repair damaged pipes/ drums.

Disclaimer: Products in this specification manual must by regulation be installed by licensed and registered trade people. The manufacturer/distributor reserves the right to vary specifications or delete models from their range without prior notification. Dimensions are nominal measurements only. Dimensions and set-outs listed are correct at time of publication however the manufacturer/distributor takes no responsibility for printing errors.

Published 12.10.2020

