

Hermetic Reciprocating Compressors

SECCP

Secop

Hermetic Reciprocating – R134a

Low, Medium and High Temperature Applications



Cat. No.	Model No.	Part No.	Displ. cm ³ /rev	Motor Type	Oil Charge cm ³	Evaporating Temperature °C													
						R134a Refrigeration Capacities Watts													
						-35	-30	-25	-23.3	-20	-15	-10	-5	0	5	7.2	10	15	
2707438	PL35G	195B3375	2.00	RSIR	150			28.0	31.6	39.3	53.0	69.4	89.0	112	140	153	172	209	
2706628	TL3G	195B3204	3.13	RSIR	280		25.3	40.9	46.7	59.1	80.5	106	136	170	211	231	258	312	
2706629	TL4G	195B3090	3.86	RSIR	280		40.8	58.3	65.3	80.3	107	140	180	226	280	306	342	413	
2706631	TL5G	195B3032	5.08	RSIR	280		55.6	79.0	87.9	107	139	178	224	278	341	372	414	497	
2706474	FR6G	195B3115	6.23	RSIR	450		47.7	83.3	96.5	124	171	226	290	365	452	494	552		
2706475	FR7.5G	195B3084	6.93	RSIR	450		61.7	99.0	113	142	193	254	325	408	505	553	618		
2706476	FR8.5G	195B3048	7.95	RSIR	450		84.9	123	138	171	228	298	381	478	592	647	722		
2707443	FR10G	195B3093	9.05	RSIR	450		91.9	136	152	188	250	324	412	516	638	697	779		
2706478	FR11G	195B3163	11.15	RSIR	450		115	170	191	233	307	395	501	628	780				
2707444	SC10G	195B3052	10.29	RSIR	550	23.0	60.0	113	135	183	268	369	486	618	764	833	925	1100	
2706539	SC12G	195B3114	12.87	RSIR	550	64.6	113	175	199	252	348	464	603	768	960	1064	1182	1437	
2706541	SC15G	195B3166	15.28	CSIR	550			164	206	290	424	568	728	908	1110	1207	1340	1600	
2706542	SC18G	195B3059	17.69	CSIR	550			283	318	394	526	684	870	1087	1337	1459	1624	1950	
2706550	SC21G	195B3005	20.95	CSR	550			333	370	453	606	792	1012	1268	1560	1700	1889	2256	

Rating Conditions: 55°C Condensing Temp., 32°C Ambient and Suction Gas Temp., 55°C Liquid Temp.