



Cylindrical screen type 305 PVC-U Screen perforations 0.5 mm

• For line strainers Type 305

d [mm]	Size [inch]	DN [mm]	kv-value ($\Delta p=1$ bar) [l/min]	Code	SP	Weight [kg]	D [mm]	L [mm]	
20	1/2	15	35	161 305 339	10	0.001	14	39	
25	3/4	20	65	161 305 389	10	0.007	18	48	
32	1	25	90	161 305 439	5	0.003	24	60	
40	1 1/4	32	155	161 305 489	2	0.004	30	71	
50	1 1/2	40	225	161 305 539	1	0.007	38	87	
63	2	50	370	161 305 589	2	0.009	48	106	
75	2 1/2	65	575	161 305 639	5	0.012	61	100	
90	3	80	955	161 305 689	2	0.016	73	118	

PF 2 31 161 998



PVC-U Inch BS

Ball valve type 375 PVC-U, with blue handle
Double union ends connection, with safe block, ASTM
solvent cement sockets

DN [mm]	L1 [mm]	d [inch]	L2 [mm]	Z [mm]	X [mm]	PN@20°C [bar]	M [mm]	S [mm]	A [mm]	H [mm]	
15	16	1/2	91	48	42	16	40	18	49	55	
20	19	3/4	103	53	48	16	45	19	59	61	
25	22	1	115	58	54	16	51	22	68	69	
32	26	1 1/4	132	68	62	16	59	26	79	81	
40	31	1 1/2	146	78	72	16	70	28	94	92	
50	38	2	168	93	86	16	84	37	115	108	

EPDM Code Code	SP	Weight [kg]	
300 141 933	1	0.130	
300 141 934	1	0.210	
300 141 935	1	0.305	
300 141 936	1	0.450	
300 141 937	1	0.695	
300 141 938	1	1.200	

PF 2 31 378 803



Double union safe block ball valve PVC-U With solvent cement sockets Inch BS

d [mm]	DN [mm]	d [inch]	PN [bar]	EPDM Code	PF	SP	Weight [kg]	
75	65	2 1/2	10	VSA22I750	2 02 956 010	8	2.200	
		3	10	VSA22L900	2 02 956 011	4	3.310	
		4	10	VSA22L910	2 02 956 011	2	5.925	

L1 [mm]	L2 [mm]	S [mm]	H1 [mm]	A [mm]	H2 [mm]	X [mm]	M [mm]	Z [mm]	H [mm]	
44	206	32		145		110	103	118	129	
		36	51	168	242	128	120	140	143	
		43	61	210	282	150	141	160	169	