
NIKLES PEARL HANDSHOWER



Dimensions are nominal measurements only.

SPECIFICATIONS	
Recommended use	Domestic, hotel and commercial
Colour availability	Chrome
Pressure rating	Suitable for high pressure applications and has been WELS certified to the following:
	Minimum operating pressure 150kPa
	Maximum operating pressure 500kPa
Temperature rating	Maximum hot temperature 60°C (recommended 42°C)
	Minimum temperature 1°C
Suitable Hot Water Units	Storage tank: Yes
	Continuous flow: Yes
	Gravity feed: Not suitable
Spray Pattern	Airdrop - Airdrop Massage

To see the complete NIKLES range go to www.reece.com.au/bathrooms

CLEANING RECOMMENDATIONS

We recommend the use of soapy water or approved cleaners. This product should not be cleaned with abrasive materials. Damage caused by any improper treatment is not covered by the product warranty refer to Warranty Conditions



In accordance with AS/NZS 6400 Licence No. 0026 Nikles Inter AG



Disclaimer: Products in this specification manual must by regulation be installed by licensed and registered trade people. The manufacturer/distributor reserves the right to vary specifications or delete models from their range without prior notification. Dimensions are nominal measurements only. Dimensions and sel-outs listed are correct at time of publication however the manufacturer/ distributor takes no responsibility for printing errors.

Tech Page Version 1

reece

NIKLES PEARL HANDSHOWER

INSTALLATION INSTRUCTIONS

