

Cabinet Coolers

Punchbowl

P Series

Features

- Suitable for all the common HFC and HCFC refrigerants including R22, R134a & R404A/R507
- Efficient inner grooved copper tubing with corrosion protected lacquer coating on return bends
- Balanced acrylic fans with ball bearing race motors
- Suitable for capillary or TX valve operation
- Epoxy coated fins



PCL Series – Low Temperature

Cat. No.	Model No.	Cap. Watts @ 6 KTD		No. of Fans	Motor Input Watts	Connections mm		Overall Dimensions mm			Defrost Heat Watts
		R404A	R22			Suct.	Liq.	Length	Width	Height	
2710408	PCL40	400	396	1	30	9.5	9.5	440	395	135	400
2710423	PCL50	500	495	1	30	9.5	9.5	440	395	135	400
2710424	PCL60	600	594	2	60	9.5	9.5	705	395	135	600
2710425	PCL80	800	792	2	60	9.5	9.5	705	395	135	600
2710426	PCL100	1000	990	3	90	9.5	9.5	840	395	135	800
2710402	PCL120*	1200	1188	3	90	12.7	12.7	840	395	135	800
2710433	PCL150*	1500	1485	3	90	12.7	12.7	840	395	190	1500
2710434	PCL170*	1700	1683	3	90	12.7	12.7	840	395	190	1500

*Fitted with 6.35mm External Equaliser