

**MTZ44-4VI****Reciprocating compressor, MTZ44HJ4BVE**

Refrigerant: R134a; R404A; R407A; R407C; R407F; R448A; R449A; R452A; R513A,
Segment usage: Air conditioning; Refrigeration MT, Compressor power supply
[V/Ph/Hz]: 400/3/50 460/3/60

PRODUCT DETAILS

Gross weight	38.5 kg
Net weight	36 kg
EAN	5702428888127
Approval standard	CCC CE UL
Brand technique	Reciprocating compressor
Capacity control	Fixed speed
Colour	Blue
Compressor power supply [V/Ph/Hz]	400/3/50 460/3/60
Configuration code	Single
Connection type	Rotolock
Cylinder	2
Description	MTZ044-4
Diameter [mm]	288 mm
Discharge connection height [mm]	74 mm
Discharge connection mounting torque [Nm]	90 Nm
Discharge connection pipe size [in]	3/4 in
Discharge connection rotolock size [in]	1 1/4 in
Discharge connection size [in]	1 1/4 in
Discharge connection sleeve pipe size [in]	3/4 in
Drawing number	8502012g
Economizer	No
Factory HP [bar]	25 bar
Factory LP [bar]	25 bar
Fitting remark	(shipped with rotolock version only)
Fitting sleeve	ODF
Fitting standard	Rotolock
Frequency [Hz]	50/60
Gauge port HP	None
Gauge port LP	Schrader
Generation code	C
Glass mounting	Threaded
Glass torque [Nm]	50 Nm
GP LP torque [Nm]	15 Nm

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Reciprocating compressor, MTZ44HJ4BVE

PRODUCT DETAILS

High side max pressure (Ps)	29.4 bar
High Side TS Max	150 °C
High Side TS Min	-35 °C
High Side Volume	0.6 L
High value of nominal voltage at 50Hz [V]	400 V
High value of nominal voltage at 60Hz [V]	460 V
High value of voltage range at 50Hz [V]	460 V
High value of voltage range at 60Hz [V]	506 V
IP protection class	IP55 (with cable gland)
Low side max pressure (Ps)	22.6 bar
Low Side TS Max	50 °C
Low Side TS Min	-35 °C
Low Side Volume	16.5 L
Low value of nominal voltage at 50Hz [V]	380 V
Low value of nominal voltage at 60Hz [V]	460 V
Low value of voltage range at 50Hz [V]	340 V
Low value of voltage range at 60Hz [V]	414 V
LRA	47 A
MCC	9.5 A
Model number	MTZ44HJ4BVE
Motor protection	Internal overload protector
Mounting torque [Nm]	15 Nm
Nominal cooling capacity at 50Hz	5.4 kW
Nominal cooling capacity at 60Hz	7.1 kW
Number of starts per hour [Max]	12
Oil charge [L]	1.8 L
Oil equalization	3/8" flare SAE
Oil equalization torque [Nm]	30 Nm
Oil reference	175PZ
Packaging height [mm]	455 mm
Packaging length [mm]	395 mm
Packaging weight [Kg]	38 kg
Packaging width [mm]	365 mm
Packing format	Single pack
Packing quantity	1
Phase	3
Power connections	Spade
Refrigerant	R134a R404A R407A R407C R407F R448A R449A R452A

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Reciprocating compressor, MTZ44HJ4BVE

PRODUCT DETAILS

	R513A
Refrigerant charge [kg] [Max]	5 kg
Relief valve	30 bar/8 bar
Rotational speed at 50Hz [rpm]	2900 rpm
Rotational speed at 60Hz [rpm]	3500 rpm
Segment usage	Air conditioning Refrigeration MT
Shipped fittings	Suction and discharge solder sleeves, rotolock nuts and gaskets
Shipped instructions	Installation instructions
Shipped mounting	Mounting kit with grommets, bolts, nuts, sleeves and washers
Shipped oil	Initial oil charge
Suction connection height [mm]	265 mm
Suction connection mounting torque [Nm]	110 Nm
Suction connection pipe size [in]	7/8 in
Suction connection rotolock size [in]	1 3/4 in
Suction connection size [in]	1 3/4 in
Suction connection sleeve pipe size [in]	7/8 in
Swept volume [cm ³]	76.22 cm ³
Technology	Reciprocating
Test dif [bar] [Max]	30 bar
Test HP [bar] [Max]	30 bar
Test LP [bar] [Max]	25 bar
Torque earth [Nm]	3 Nm
Torque power [Nm]	3 Nm
Total height [mm]	413 mm
Type	MTZ
Type designation	Compressor
Winding resistance for three- phase compressors with identical windings [Ohm]	3.29 Ohm

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Accessories



7750009 [🔗](#)

Discharge thermostat kit

Discharge thermostat kit

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**8156132** [🔗](#)**Gasket, 1-3/4"**

Gasket, 1-3/4"

**8156131** [🔗](#)**Gasket, 1-1/4"**

Gasket, 1-1/4"

**8153008** [🔗](#)**Adaptor**

Solder sleeve, P04 (1-1/4" rotolock, 3/4" ODF)

**8156009** [🔗](#)**Gasket set, 1", 1-1/4", 1-3/4", OSG gaskets black and white**

Gasket set, 1", 1-1/4", 1-3/4", OSG gaskets black and white

**8156134** [🔗](#)**Service kit for terminal box 80 x 96 mm, including 1 cover, 1 clamp**

Service kit for terminal box 80 x 96 mm, including 1 cover, 1 clamp

**8153013** [🔗](#)**Adaptor**

Solder sleeve, P07 (1-3/4" rotolock, 7/8" ODF)

**120Z0638** [🔗](#)**POE lubricant, 175PZ, 1-litre can**

POE lubricant, 175PZ, 1-litre can

**120Z0576** [🔗](#)**Acoustic hood for two-cylinder compressor**

Acoustic hood for two-cylinder compressor

**120Z0639** [🔗](#)**POE lubricant, 175PZ, 2.5L CAN**

POE lubricant, 175PZ, 2.5L CAN

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Spare Parts



7773107 [↗](#)

Belt type crankcase heater, 65 W, 230 V, CE mark, UL

Belt type crankcase heater, 65 W, 230 V, CE mark, UL



7773117 [↗](#)

Belt type crankcase heater, 65 W, 400 V, CE mark, UL

Belt type crankcase heater, 65 W, 400 V, CE mark, UL



8156145 [↗](#)

Gasket for oil sight glass (black chloroprene)

Gasket for oil sight glass (black chloroprene)



7705006 [↗](#)

MCI

Electronic soft start kit, MCI 15 C



120Z0459 [↗](#)

PTC heater 27W, CE mark, UL

PTC heater 27W, CE mark, UL



7703006 [↗](#)

Valve set

Packing format: Multi pack, Packing quantity: 6



8168032 [↗](#)

Rotolock valve, V07 (1-3/4" rotolock, 7/8" ODF), Service kit

VALVE SETS V07 1 3/4"-7/8"



8156019 [↗](#)

Oil sight glass with gaskets (black and white)

Oil sight glass with gaskets (black and white)



8168029 [↗](#)

Rotolock valve, V04 (1-1/4" rotolock, 3/4" ODF), Service kit

VALVE SETS V04 1 1/4"-3/4"

For more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Spare Parts



120Z0466 [🔗](#)

Belt type crankcase heater, 65 W, 460 V, CE mark, UL

Belt type crankcase heater, 65 W, 460 V, CE mark, UL

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.