

Cabinet Coolers

Punchbowl

P Series

Features

- Suitable for all the common HFC and HCFC refrigerants including R22, R134a & R404A/R507
- Efficient inner grooved copper tubing with corrosion protected lacquer coating on return bends
- Balanced acrylic fans with ball bearing race motors
- Suitable for capillary or TX valve operation
- Epoxy coated fins



PC Series – Medium Temperature

| Cat. No. | Model No. | Cap. Watts @ 6 KTD | | | No. of Fans | Motor Input Watts | Connections mm | | Overall Dimensions mm | | |
|----------|-----------|--------------------|-------|------|-------------|-------------------|----------------|------|-----------------------|-------|--------|
| | | R404A | R134a | R22 | | | Suct. | Liq. | Length | Width | Height |
| 2710404 | PC30 | 313 | 295 | 310 | 1 | 30 | 9.5 | 9.5 | 440 | 395 | 135 |
| 2710405 | PC41 | 414 | 390 | 410 | 1 | 30 | 9.5 | 9.5 | 440 | 395 | 135 |
| 2710406 | PC53 | 535 | 504 | 530 | 1 | 30 | 9.5 | 9.5 | 440 | 395 | 135 |
| 2710407 | PC64 | 646 | 608 | 640 | 1 | 30 | 9.5 | 9.5 | 440 | 395 | 135 |
| 2710409 | PC76 | 768 | 722 | 760 | 2 | 60 | 9.5 | 9.5 | 705 | 395 | 135 |
| 2710410 | PC100 | 1030 | 969 | 1020 | 2 | 60 | 9.5 | 9.5 | 705 | 395 | 135 |
| 2710411 | PC135 | 1364 | 1283 | 1350 | 3 | 90 | 9.5 | 9.5 | 840 | 395 | 135 |
| 2710412 | PC160* | 1616 | 1520 | 1600 | 3 | 90 | 12.7 | 12.7 | 840 | 395 | 135 |
| 2710413 | PC200* | 2020 | 1900 | 2000 | 3 | 90 | 12.7 | 12.7 | 840 | 395 | 190 |
| 2710414 | PC230* | 2323 | 2185 | 2300 | 3 | 90 | 12.7 | 12.7 | 840 | 395 | 190 |

*Fitted with 6.35mm External Equaliser