

# Pleated Carbon JUMBO filter cartridge



2 High

1 High



Pleated Carbon filter cartridges are designed for high flow and / or low pressure applications. Very suitable for rainwater tanks. Pleated cartridges do not provide the same contaminant removal performance of standard 'depth' type filter cartridges.

## Specifications

- Micron rating: 10 micron (nominal)
- Materials of construction: Polyfin fibres and activated carbon
- Temperature range: 4 – 40°C (not for use in hot water)
- Duty: CP for reduction of sediment, chlorine, taste/odour, & organic matter
- Flow rate: <30 lpm 1 high | <50 lpm 2 high
- Filter cartridge change: 12 months max
- Length: 254mm or 508mm
- Diameter: 110mm

## Features & Benefits

- High surface area – low pressure drop and high flow rates
- Individually wrapped, sealed and labelled
- Pure polypropylene construction - food grade
- Competitive value product
- Food Grade - Polyolefin fibre and activated carbon

## Application

- Domestic Whole House System
- Commercial high flow
- Light industrial
- Chemical - check compatibility
- Prefiltration
- Sea water

CODE	REECE CODE	MICRON	HIGH	LENGTH	WIDTH
CP10W	1911243	10	1	254mm	114mm
CP10W20	1911244	10	2	508mm	114mm