



Ghost™ Internal Mini-Split Condensate Pump



- Advanced Diaphragm Pump
- Quiet – Variable speed operation
- Discreet – Designed to fit inside the evaporator. Univolt model
- Reliable – No piston, no anti siphoning device

Advanced. Quiet. Discreet. Reliable.



mini-split condensate pump

Code	Description	Qty
83799	Ghost Internal	1



FEATURES

- Advanced Diaphragm Pump Technology
- Quiet – Variable speed operation
- Discreet – Easy to install, Univolt model
- Reliable – No piston, no anti siphoning device
- Reservoir connected directly to OEM drain spout
- Overflow switch connection
- Thermally protected pump
- Resettable fuse
- Kits include all required components

Application

Ghost Internal minipump is for installation inside casing of mini-split evaporator, above ceiling or inside lineset cover. Concealed to preserve a clean finished appearance.

Recommended for

- Mini-split systems, residential or commercial

Capacity	Up to 54,500 BTU/HR or 15.97 kW 11 GPH; 41.6 LPH
----------	---

Max Recommended Head	50 ft / 15.2 M
----------------------	----------------

Maximum Water Temp	104°F / 40°C
--------------------	--------------

Suction Lift	5 ft; 1.52 M
--------------	--------------

Sound Level	@ 39" < 21 db(A); @ 1 M < 21 db(A)
-------------	------------------------------------



RectorSeal, LLC • 2601 Spenwick Drive, Houston, TX 77055, USA • 800-231-3345 rectorseal.com
RectorSeal Australia Pty Ltd. • PO Box 5092 Hoppers Crossing, VIC 3029, Australia • 07 3267 7277 rectorseal.com.au

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2020 RectorSeal. All rights reserved. R50518-1120