

# Filter Driers



## Emerson

### CSFD Compact Suction Line Burnout Filter-Drier

The CSFD compact suction line filter-drier is used in applications where other driers won't fit. It is primarily used to remove contamination after a burnout and is designed for short lay-ins. It removes moisture, acid and contaminants and is suitable for CFC, HCFC and HFC refrigerants.



Cat. No.	Part No.	Solder Connection	Suction Line Flow Capacity kW													
			Evaporating Temperature °C													
			R134a				R22					R404A, R507				
			4	-7	-18	-29	4	-7	-18	-29	-40	4	-7	-18	-29	-40
2708513	CSFD14S4V V	1/2"	4.6	3.2	1.7	1.0	7.0	4.6	3.2	2.1	1.0	4.6	2.8	1.7	1.05	0.7
2708514	CSFD14S5V V	5/8"	8.1	5.3	3.1	1.7	12.7	8.4	5.6	3.5	1.7	9.1	5.9	3.9	2.46	1.0
2708515	CSFD14S6V V	3/4"	10.9	7.7	4.9	2.5	17.2	11.2	7.7	4.9	2.5	12.7	8.1	5.3	3.16	1.8
2708516	CSFD14S7V V	7/8"	11.6	7.7	4.9	2.5	18.3	11.9	8.1	5.3	2.8	12.7	8.1	5.3	3.16	1.8
2708517	CSFD14S9V V	1 1/8"	15.8	10.5	6.3	3.5	24.6	16.2	10.9	7.0	3.5	17.2	10.9	7.0	4.57	32.5