

UV20



6

BWT Multistage UV System - UV20

SEDIMENT, ACTIVATED CARBON AND ULTRAVIOLET DISINFECTION SOLUTION

DBWT

BWT UV20

BWT Multistage UV System – UV20

Harnessing the power of ultraviolet light, this unit acts as a natural and chemical free solution to disinfecting mains water and provides an enhanced water experience.

STAGE 1 Sediment filtration to reduce dirt/ rust, sediment and particulate matter

0



STAGE 2 Activated carbon cartridge to reduce bad taste & odours and organic matter STAGE 3 Ultraviolet lamp with a quartz glass sleeve all contained within a stainless steel pressure vessel

UV20

Features

- 3 Stage UV Filter System turns your mains or tank water into clean, safe potable water
- Supplied on a manifold bracket
- Quality design and materials of construction for performance and longevity
- Lockable cover protects controller and lamp replacement cap
- BWT controller monitors lamp life with a countdown timer. A handy 2 stage alarm provides a call to action

Applications

Rainwater tank




Commercial




Product Dimensions

Note: For cartridge change allow 200mm beneath system. For UV lamp change allow 1000mm above system.



22



DEWT

Specifications		
Model:	BWT UV20	
Connection:	1" bspf (inlet) 1" bspm (outlet)	
Water Pressure:	300 kPa min - 860 kPa max	
Water Temperature:	4 deg C - 40 deg C (Protect from freezing)	
Flow Rate:	< 70 lpm (30mJ/cm2)	

Spares		
Stage 1 filtration:	PL10W20	
Stage 2 filtration:	CP10W20	
Stage 3 Ultra violet disinfection:	UV lamp UV20LP56 UV Quartz Sleeve UV20QS1	

Maintenance Guidelines

For optimum performance of the UV20 – Replace the UV lamp annually. 9000 hours (12 months) life is set on controller alarm for convenience. Periodically clean the quartz sleeve to remove staining. Changeout of filter cartridges is recommended every 12 months.



Warranty

BWT Australia warrants that the products supplied will be free from any defects in workmanship or materials for 12 months from the date of purchase. Further, the warranty provided herein applies only when products are installed in accordance with installation instructions, used within the product specifications and service life; beyond which time or use BWT is absolved of any and all liability for any use of the product. No liability is accepted where pressure, temperature or in the event of defect or non-conformity, buyer shall properly notify BWT in writing, supplying proof of purchase dates, installation dates, and will protect and retain the products for investigation. There are no other warranties, either merchantability or fitness, either expressed or implied except as excluded by law.