

Product Specification Information

Sizes

15mm, 22mm, 28mm, 35mm, 42mm, 54mm

Performance

Maximum pressure: 1600kPa

Temperature range: -35°C to +110°C

Applications

Refer to >B< Press Stainless Steel technical guide for suitable applications, or contact support@conexbanninger.com.au to confirm compatibility



Product Specification

A – Specification Statement

Fittings for Stainless Steel Tube

Conex Bänninger >B< Press Stainless Steel 3-point press fittings shall be installed and tested by a licenced plumber following the manufacturer's installation instructions and according to AS/NZS 3500. The fittings shall include lead-in edge seal protection and have a maximum working pressure of 1600kPa between temperatures of -35°C to +110°C. Factory fitted elastomeric seals shall be made of black EPDM material and be manufactured with an in-built leak before press O-ring indicator. The fitting joints shall be made with pressing tools and jaw sets recommended and approved by Conex Bänninger. Installer training and advice should be requested at www.conexbanninger.com.au

C – Summary Specification

Fittings for Stainless Steel Tube

Stainless Steel press fittings shall be Conex Bänninger >B< Press Stainless Steel 3-point press with black EPDM O-ring. The fittings shall be installed and tested by a licenced plumber following the manufacturer's installation instructions and according to AS/NZS 3500. Installer training and advice should be requested at www.conexbanninger.com.au

B – Product Specification Points

Fittings for Stainless Steel Tube

- Fittings shall comply with AS 3688:2016 and be approved by WaterMark certification
- Stainless steel press fittings shall be compatible with stainless steel tube manufactured to AS 5200.053
- Conex Bänninger >B< Press Stainless Steel 3-point press fittings shall be installed and tested by a licenced plumber following the manufacturer's installation instructions and according to AS/NZS 3500
- Fittings shall be manufactured from 316L stainless steel and have lead-in edge seal protection
- Fittings shall have a maximum working pressure of 1600kPa between temperatures of -35°C to +110°C
- Factory fitted elastomeric seals shall be made of black EPDM material and be manufactured with an in-built leak before press O-ring indicator
- The fitting joints shall be made with pressing tools and jaw sets recommended and approved by Conex Bänninger
- Installer training and advice should be requested at www.conexbanninger.com.au