



Your window to  
a perfect climate.

**kaden**<sup>®</sup>  
your perfect climate

[www.kadenair.com.au](http://www.kadenair.com.au)

Your simplest climate control

# Kaden Window Air Conditioner

Specifically designed for the Australian climate, the Kaden Window Air Conditioner offers a simple climate solution which provides comfort to you during harsh summers and chilly winters alike.



## The Kaden difference

### Wi-Fi enabled

Easily control your Kaden unit from your smartphone wherever you are.

### Increased efficiency

New R32 refrigerant reduces energy consumption and is less harmful to the environment.



### Enhanced durability

Anti-corrosive Blue Fin technology keeps your unit protected in tough conditions.

### Healthy home

Advanced silver ion filter reduces and breaks down harmful bacteria and contaminants in the air, keeping your home safe and healthy.

### Wireless Remote

With a classic design and large, clear LCD display, the Kaden wireless remote is optimised for ease of use.



Check Filter Indicator



Fresh Air Function



Timer



Sleep Function



Self Diagnostics



Auto Swing Air Direction



3D Airflow



3 Fan Speed with Auto Mode

\*Control your Kaden unit wherever you are with Wi-Fi included in every model

			KW09	KW12	KW18	KW21
Power supply	PH- V - Hz		1 Phase, 220-240V, 50Hz			
Recommended Circuit Breaker		(A)	10	10	15	15
Rated Current		(A)	5	7.5	10.7	13.2
Capacity	Cooling	kW	2.75	3.90	5.30	6.00
	Heating	kW	2.45	3.60	4.80	5.52
Input	Cooling	kW	0.83	1.18	1.60	1.81
	Heating	kW	0.74	1.06	1.45	1.69
Power Current	Cooling	(A)	3.63	5.13	7.87	7.87
	Heating	(A)	3.25	4.53	7.35	7.35
Star Rating: Hot / Average / Cold	Cooling		2.0 / 1.5 / 1.5	1.5 / 1.5 / 1.5	2.0 / 1.5 / 1.5	1.5 / 1.5 / 1.5
	Heating		1.0 / 0.5 / 0.5	1.0 / 1.0 / 0.5	1.0 / 0.5 / 0.5	1.0 / 0.5 / 0.5
EER	Cooling		3.33	3.31	3.31	3.31
COP	Heating		3.31	3.40	3.31	3.26
Sound Pressure Level (Hi, Med, Low)	Indoor	dBA	50-48-46	50-48-46	55-53-51	56-54-52
	Outdoor	dBA	57-55-53	60-58-56	63-61-59	64-62-60
Airflow		l/sec	133	186	264	264
Dimensions (H x W x D)		mm	375x560x668	428x660x700	428x660x770	428x660x770
Net Weight		kg	40	51	64	65
Dehumidifying Volume		l/hr	1.00	1.50	2.20	2.20
Refrigerant	Type		R32			
	Quantity	kg	0.60	0.86	1.08	1.05
Outdoor Operating Range	Cooling	°C	18~43	18~43	18~43	18~43
	Heating	°C	-7~30	-7~30	-7~30	-7~30

**kaden°**  
your perfect climate

## Warranty

Kaden is committed to total customer care, so you'll enjoy market-leading warranties and ongoing after-sales support. The Kaden range offers a 5 year warranty on parts and labour for residential and light commercial.



Residential & Commercial  
Parts & labour



Non-human comfort  
Parts & labour

**kadenair.com.au**

Due to limitations in the printing process the colours in this brochure are a guide only. The manufacturer/distributor reserves the right to vary specifications or delete models from their range without prior notification. The manufacturer/distributor takes no responsibility for printing errors. All products enjoy a product replacement warranty. For full warranty details visit [www.kadenair.com.au](http://www.kadenair.com.au)

metalflex™

ACTROL™

