

NEW

ROAIRVAC R32 2.0/5.0 CL

Battery-driven, two stage vacuum pump



BATTERY-POWERED

Powered by CAS batteries
up to 90 min. on one charge

VACUUM-STABLE

Integrated magnetic valve keeps the
vacuum even when the battery is empty

COMPACT

Lighter and stronger than comparable
wired vacuum pumps

ROAIRVAC R32 2.0/5.0 CL



Gas ballast valve

Reduction of water vapour in the oil container, guarantees higher evacuation power and service life.¹⁾

Special filter

Reduces oil mist on exhaust vent

Ergonomic handle

Light, compact and easy to transport

CAS battery

Compatible with more than 160 power tools from 17 manufacturers

Light and high-quality casing

Protects the integrated components



One battery, many solutions.

Founded in 2018, 17 manufacturers are already using the Cordless Alliance System, CAS for short, as of September 2020. CAS is the first cross-manufacturer battery system.

Model	 kg	No.
ROAIRVAC R32 2.0 CL	3.7	1000003230
ROAIRVAC R32 5.0 CL	7.5	1000003233

ROAIRVAC R32 2.0 CL

Technical data

Pump rating	2.0 CFM / 57 l/min
Vacuum stages	2
Final vacuum	23 micron
Motor power	185 W / 3,600 r/m
Voltage	18 V
Connection	1/4"
with Adapter	5/16" SAEM / 3/8" SAEM
Oil capacity	180 ml

ROAIRVAC R32 5.0 CL

Technical data

Pump rating	5.0 CFM / 142 l/min
Vacuum stages	2
Final vacuum	15 micron
Motor power	550 W / 1,800 r/m
Voltage	18 V
Connection	1/4"
with Adapter	5/16" SAEM / 3/8" SAEM
Oil capacity	350 ml

1) Only applies to ROAIRVAC R32 5.0 CL