



**Strong & solid**

**Highest load rating\***

**Easy installation**

**Virtually indestructible**

**10 year warranty**

**100% recycled plastic**

**Maintenance free**

**UV stable & weatherproof**

**Versatile uses**

**Australian made & owned**

## Our Air Con Mounting Blocks are ideal for ground mounting air conditioner compressors on a strong, durable base

- Highest load rating in the industry - 5 to 13 tonnes maximum per block\*
- Virtually indestructible - will not crack, collapse or rust
- Made from 100% recycled plastic & coffee cups - eco friendly
- Strong, solid & stable
- Maintenance free
- Weatherproof & UV stabilised
- Easy installation, no assembly required
- Australian made & owned, with a 10 year warranty<sup>2</sup>
- Impact resistant & lightweight compared with concrete pads
- Maximises air flow & water drainage to aid unit longevity
- Helps absorb vibrations for quieter operation
- Recyclable at end of life
- Ideal for level or uneven ground & flat deck roofs
- Suitable for most split system air conditioner units
- May be used for generators, pool heaters, rainwater tanks etc
- Dimensions: 90mm (w) x 90mm (h)      Colour: Off White or Black

Length	380mm	450mm	600mm	1000mm
Max loading per block*	5 tonnes	6 tonnes	8 tonnes	13 tonnes
Weight of block	1.5kg	1.8kg	2.4kg	4kg
Shipping Pack- blocks	16	14	10	6

\* With weight evenly distributed      325kg per 25mm cross section (approx)

- Place mounting block on stable ground in a capital I orientation. Fix unit to centre of each mounting block with a screw & washer suitable for an outdoor application (not included). May also be fixed to ground.

**WARNINGS** Product is not suitable for wall mounting or for free spanning. Non-structural product. Product should only be installed by a suitably qualified person with the unit disconnected from mains supply. Always check with the manufacturer's installation instructions for correct unit placement. **Warning:** Always perform your own risk assessment before using this product. Always know the weight of the equipment being supported. Never exceed the maximum loading. Under no circumstances does the maximum loading mentioned above take into consideration point loading or uneven weight distribution of the supported load. > Warranty limited to product replacement, where failure is due to a manufacturing fault and the product was installed according to instructions provided above. Dated proof of purchase is required. Excludes any colour fading which may occur with prolonged UV exposure. \*\* NOT TO BE USED FOR SUPPORTING MOBILE PLANT AND EQUIPMENT\*\*

📧 [sales@plasticforests.com.au](mailto:sales@plasticforests.com.au)    ☎ (02) 6048 0532    📍 21 Union Road North Albury NSW 2640

**DISCLAIMER:** All information provided in this publication is correct to the best knowledge of the company and is given out in good faith. The information presented herein is intended only as a general guide to the use of such products and no liability is accepted by Plastic Forests Pty Ltd for any loss or damage however arising, which results either directly or indirectly from the use of such information. Users of products made from recycled plastic should recognise the limitations imposed, and in conjunction with the supplier agree on the necessary specification limits. In general, products made from recycled plastic conform to "Fit for Use" criteria. Information and product specifications may change without notice. 04112023    ACN: 147 913 559    ABN: 991 479 13559

Recycled and manufactured by