

PRO75 SERIES SIDE INLET VALVES

TECHNICAL DATA

Operating Pressure: 2.6 - 232 psi (0.18 - 16 Bar), (18 - 1,600 kPa)

Critical Level: 35.5mm (1.4")

Flow Range: .50 gpm (2.3 L/min) minimum @ 2.6 psi (0.18 Bar), (18 kPa)
8 gpm (36.4 L/min) maximum @ 150+ psi (10.3 Bar), (1,034 kPa)

Sound Level: 32 dBA

Float Adjustment Range: 114.3mm (4.5")

Durability: 250,000+ Flushes



FEATURES

Fast refill & ultra quiet design

Compact size fits a wide range of applications (Including small in-wall tanks)

Unique self-cleaning valve design operates from VERY LOW to HIGH pressures

Proven & reliable quality



Reduces water hammer

Harsh water durability

Easy install

Heavy duty brass shank (PRO75B Option)

5 year warranty



PRO75B



Quality, Craftsmanship, Integrity:

Fluidmaster's® PRO Series is for the hardworking plumbing professional who requires high quality, professional grade products that have been engineered for reliability and durability.



Fluidmaster Holdings Australia Pty Ltd
5B/100 New Street, Ringwood
Victoria 3134
Ph(03) 88702555 Fax(03) 88702566
Email: Salesau@fluidmaster.com
www.fluidmaster.com.au



30800 Rancho Viejo Road
San Juan Capistrano, CA 92675
www.Fluidmaster.com

FM91595, GREV1, 08/2016