

Hermetic Reciprocating Compressors

SECCP
Secop
Hermetic Reciprocating – R134a

Low and Medium Temperature Applications



Cat. No.	Model No.	Part No.	Displ. cm ³ / rev	Motor Type	Oil Charge cm ³	Evaporating Temperature °C								
						R134a Refrigeration Capacities Watts								
						-35	-30	-25	-23.3	-20	-15	-10	-5	0
2706630	TL5F	195B3377	5.08	RSIR	180	43	60	82	91	110	144	183		
2707414	TLS6F	195B3047	5.70	RSIR	180	58	77	104	115	139	183	235		
2707415	NL6F	195B3370	6.13	RSIR	320	52	77	110	123	151	200	258		
2707422	NL7F	195B3380	7.27	RSIR	320	71	99	136	151	182	238	303		
2706518	NL9F	195B3369	8.35	RSIR	320	80	112	155	172	208	272	346		
2706517	NL11F	195B3381	11.15	RSIR	320	102	144	200	223	271	356	455		
2706540	SC15F	195B3230	15.28	RSIR	550	100	155	230	260	325	439	573		
2707418	SC18F	195B3216	17.69	CSIR	550	129	194	280	314	388	518	669	842	
2707416	SC21F	195B3215	20.95	CSIR	550	185	245	335	375	455	610	780	990	

Rating Conditions: 55°C Condensing Temp., 32°C Ambient and Suction Gas Temp., 55°C Liquid Temp.