

Z-80300
WALL BIB TAP

Dimensional Data (mm) are subject to manufacturing tolerances and change without notice



**THIS VALVE MUST BE
INSTALLED AT
350kPa**

ENGINEERING SPECIFICATION

- Chrome plated slow closing bib tap
- Vandal resistant handle
- Easily adjusted time cycle
- Screw-down top access panel

PRODUCT INFORMATION**Z-80300 FEATURES**

Min. Inlet Pressure - 150kPa


Max. Inlet Pressure - 350kPa

Max. Temperature - 60 degrees

Time Cycle Adjust - 5 to 8 seconds

STANDARDS COMPLIANCE

- Australian Watermark Approved - WM-021242
- WELS Registration No. T41091
- WELS Rating - 6 Star - 2.0L

**TIME CYCLE INFORMATION**

If time cycle adjustment is necessary remove set screw from handle nut and handle to expose white adjustment nut. To increase the time cycle, turn the adjustment nut in a clockwise direction. Replace handle after each adjustment to test until the desired time is achieved.

AS/NZS 3500.1.2003**3.3.4 'Maximum Pressure Within Buildings'**

Provision shall be made to ensure that the maximum operating pressure at any outlet, other than a fire service outlet, within a building **DOES NOT EXCEED 350kPa.**