

## THERMANN<sup>™</sup> **Integrated Heat Pump R290**

Page 01 of 01







Dimensions (mm)				
MODEL	200L	285L		
Inlet Height (A)	200	200		
Outlet Height (B)	950	1375		
Total Height (C)	1580	2005		
Total Diameter (D)	620	620		
Total Depth including Cover (E)	665	665		

**Specifications** 

YEAR YEAR AND GUARANTE	
Tonk	

WARRANTY



Tank

Refrigeration

Components

Labour

Tank Labour

5L	
7	1
6	
.6	
/290	



Other Parts & Labour

- P				
MODEL	200L	285L		
Storage Capacity (L)	202.5	287		
Rated Energy Input (kW)	2.6	2.6		
Max Current (A)	12.6	12.6		
Heating capacity# (kW)	2.5			
Refrigerant Type/Mass (g)	R290/270	R290/290		
Net Weight (kg)	90	125		
Max. Refrigerant Circuit Pressure (kPa)	2600			
Relief Valve Rating	1000kPa/10kW			
Operating Ambient	-6°C to 45°C			

## Temperature Notes:

- (1). Water heater operates using electric heating element outside of the operating ambient temperature range.
- (2). Hard-water anode models available.
- (3). Suitable for outdoor installation only.
- (4). Warranty terms and conditions apply.
- (5). Refer instructions provided with the product for full details on the product specifications, installation, operation and warranty.
- (6). Based on from 20°C to 60°C water temperature rise at 20°C ambient air temperature.

Disclaimer: Products in this specification manual must by regulation be installed by licensed and registered trade people. The manufacturer/distributor reserves the right to vary specifications or delete models from their range without prior notification. Dimensions are nominal measurements only. Dimensions and set-outs listed are correct at time of publication however the manufacturer/distributor takes no responsibility for printing errors.