

Mizu Drift Mk2 Wall Basin Mixer Set (4*)

IMPORTANT NOTE:

Mixer must be installed to the requirements of AS/NZS 3500 by a qualified plumber. Your mixer comes to you already factory assembled and tested. We do not recommend the dismantling of any internal part of the mixer. The mixers are factory tested and sealed so as to give the best performance.

INSTALLATION INSTRUCTIONS:

1. Flush out new pipe work prior to connecting the new mixer.
2. During installation, protect the cartridge sleeve (7) surface and spout outlet hole by using the plastic cover (22) and plug provided. Pay attention to the mixer and cover plate dimensions when working out installation depth. If required, manipulate the mounting surface to allow for a suitable installation depth.
3. The mixer is ideally suited for timber/metal noggin installation using fastening screws for mounting. If an alternative installation method is intended (e.g. block wall) take appropriate steps to ensure a suitable installation.
4. The outlet in the mixer must always be to the left of the operation handle and aligned level.
5. Connect the hot water supply line to the hot 'H' inlet and the cold water supply line to the cold 'C' inlet in the mixer.
6. Pressure test all connections as to AS/NZS 3500.
7. After the finished wall is completed, remove both the plastic covers.
8. Apply Teflon tape on the spout adapter (20) and use an 8mm Allen key (not supplied) to tighten the adapter into the mixer outlet threads. Ensure appropriate allowance is given for thread engagement and offset for the spout fitment.
9. Fit the wall cover plate (5) and use an appropriate sealing compound to seal the cover plate edges to the wall.
10. Fit the spout (16) by placing it over the spout adapter end that is exposed and secure the spout by tightening the 2 grub screws (17) in the spout with the supplied Allen key (21).
11. Fit the handle (11)(14) by fitting the handle slot over the mixer cartridge (8) lever. Use the supplied Allen key (21) to tighten the grub screw (12) in the handle till it is firmly secured. Insert the grub screw hole cover (13) into the handle.

NOTE: Do not over tighten hose tail into the mixer

Do not twist hose braiding to tighten hoses

Do not use Teflon tape or thread locking compounding on any of the threaded connections

CLEANING RECOMMENDATIONS:

We recommend the use of soapy water or approved cleaners. This product should not be cleaned with abrasive materials. Damage caused by any improper treatment is not covered by the product warranty. Refer to Warranty Conditions